

SIMATIC CFast memory card, 128 GB, for IPCs with corresponding slot  
Further information, quantity and content: See technical data



Figure similar

General information	
Product type designation	CFast memory card
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	3.3 V; $\pm 5\%$
Input current	
Current consumption (rated value)	100 mA; Typical
Power	
Active power input, typ.	1.1 W; Inactive 0.4 W
Memory	
Type of memory	CFast Type I
Memory size	128 Gbyte; 1 year (data retention)
Speed class	Write speed: up to 200 MB/s (UDMA6), read speed: up to 100 MB/s (UDMA6)
Write cycles MLC flash	8.8; Terabytes, industrial quality
Wear leveling (distributed writing)	Yes
Write protection switch	No
Interfaces	
Interfaces/bus type	Serial ATA
Standards, approvals, certificates	
CE mark	Yes; Certificates, Declaration of Conformity can be downloaded from SIOS, for commodities directly from the manufacturer
EAC (formerly Gost-R)	Yes
RoHS conformity	Yes
Use in hazardous areas	
<ul style="list-style-type: none"> <li>• ATEX Zone 2</li> <li>• ATEX Zone 22</li> <li>• IECEx Zone 1</li> <li>• IECEx Zone 11</li> <li>• IECEx Zone 2</li> <li>• IECEx Zone 22</li> <li>• cULus Class I Zone 1</li> <li>• cULus Class I Zone 2, Division 2</li> <li>• cULus Class II Division 2</li> <li>• FM Class I Division 2</li> <li>• FM Class II Division 2</li> </ul>	<ul style="list-style-type: none"> <li>Yes; Always comply with the operating instructions of the target device.</li> <li>Yes; Always comply with the operating instructions of the target device.</li> <li>No</li> <li>No</li> <li>Yes; Always comply with the operating instructions of the target device.</li> <li>Yes; Always comply with the operating instructions of the target device.</li> <li>Yes; Always comply with the operating instructions of the target device.</li> <li>Yes; Always comply with the operating instructions of the target device.</li> <li>Yes; Always comply with the operating instructions of the target device.</li> <li>Yes; Always comply with the operating instructions of the target device.</li> <li>Yes; Always comply with the operating instructions of the target device.</li> </ul>
Marine approval	
<ul style="list-style-type: none"> <li>• Germanischer Lloyd (GL)</li> </ul>	Yes; Always comply with the operating instructions of the target device.

- American Bureau of Shipping (ABS)
- Bureau Veritas (BV)
- Det Norske Veritas (DNV)
- Korean Register of Shipping (KRS)
- Lloyds Register of Shipping (LRS)
- Nippon Kaiji Kyokai (Class NK)
- Polski Rejestr Statkow (PRS)
- Chinese Classification Society (CCS)

Yes; Always comply with the operating instructions of the target device.  
 Yes; Always comply with the operating instructions of the target device.  
 Yes; Always comply with the operating instructions of the target device.  
 Yes; Always comply with the operating instructions of the target device.  
 Yes; Always comply with the operating instructions of the target device.  
 Yes; Always comply with the operating instructions of the target device.  
 Yes; Always comply with the operating instructions of the target device.  
 Yes; Always comply with the operating instructions of the target device.

Ambient conditions	
Suited for indoor use	Yes; Always comply with the operating instructions of the target device.
Suited for outdoor use	Yes; Always comply with the operating instructions of the target device.
Ambient temperature during operation	
• min.	0 °C; Any mounting angle
• max.	55 °C; Any mounting angle
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Relative humidity	
• Operation, max.	85 %
• Condensation permissible	No
Accessories	
Function description	fixed mode, multiple partitions possible
Mechanics/material	
Enclosure material (front)	
• Plastic	Yes
Dimensions	
Width	42.8 mm
Height	36.4 mm
Thickness	3.6 mm
Weights	
Weight (without packaging)	10 g
Weight (with packaging)	20 g
Other	
Merchandise	No
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Target devices	Suitable for IPC and HMI devices with the corresponding interfaces (see manual)
Note:	bootable, real-time capable, error correction, wear leveling, power loss protection and diagnostics-capable

last modified:

3/12/2021 