## TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

### UPS Replacement 36VDC Battery Cartridge for select Tripp Lite SLT UPS

#### MODEL NUMBER: RBC36-SLT



#### Description

Tripp Lite's premium UPS replacement battery cartridges breathe new life into UPS systems suffering from expired or weak internal batteries. Each replacement battery cartridge is carefully screened and certified to meet or exceed original specifications, and ships ready for installation into your UPS system. Reusable packaging holds expired batteries for recycling center delivery. See Tripp Lite's UPS replacement battery web page to confirm compatibility and quantity required. Compatible with Tripp Lite models SMART1500, SMART1500SLT, SMX1500SLT (versions with preassembled 3-battery cartridges only; see compatibility listing for non-assembled battery versions)

#### Features

- Restores UPS runtime performance to original specifications
- Comes pre-assembled and ready for installation
- Reusable packaging holds expired batteries for recycling center delivery

### **Specifications**

OVERVIEW		
	027220427426	
UPC Code	037332127136	
BATTERY		
DC System Voltage (VDC)	36	
Included Battery Set	Contains (3) 12V 9AH sealed lead acid batteries	
Typical Battery Lifespan	3-5 years, depending on UPS operating conditions	
PHYSICAL		
Shipping Dimensions (hwd / in.)	4.60 x 6.50 x 11.40	

#### Highlights

- Tripp Lite-certified premium battery cartridge
- Pre-assembled and wired battery kit offers simple installation
- Rugged leak-proof construction
- Maintenance free
- Wide operating temperature range

#### **Package Includes**

 One pre-assembled battery pack consisting of three 12V batteries

# TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

Shipping Dimensions (hwd / cm)	11.68 x 16.51 x 28.96
Shipping Weight (lbs.)	19.30
Shipping Weight (kg)	8.75
Unit Dimensions (hwd / in.)	4.000 x 6.000 x 7.500
Unit Dimensions (hwd / cm)	10.16 x 15.2 x 19.1
Unit Weight (Ibs.)	18.8
Unit Weight (kg)	8.53
ENVIRONMENTAL	
Relative Humidity	0-95% NON-CONDENSING
Operating Elevation (ft.)	0-10,000 FEET
Storage Elevation (ft.)	0-50,000 FEET
Operating Elevation (m)	0-3000 m
Storage Elevation (m)	0 - 15,200 m
STANDARDS & COMPLIANCE	
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (U.S. & Canada)	18-month limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty



© 2022 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.