



## Fused Terminal Blocks

### 1003 SI/ 1 DS GW

screw terminal block with fuse holder 6,3x25/6,3x32, 1 pole, wire protector (DS): yes, cross-section rating: 4.0 mm<sup>2</sup>, voltage rating: 500 V, current rating: 16 A



#### Order Info

reference number (ref.no.)	11618
PU	100
EAN	4028012143993

#### Type

type	screw terminal block with fuse holder 6,3x25/6,3x32
number of poles	1 pole
clamping units per pole	1
colour	natural
cross-section rating	4.0 mm <sup>2</sup>
connection type	screw
wire protector (DS)	yes

#### Technical Data

voltage rating	500 V
current rating	16 A
insulating material	PA GW
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	4.0 mm <sup>2</sup>
flammability rating	V-2
min. ambient temperature	-40 °C
max. ambient temperature operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.5-8.0 mm
assembly contact screw	0,8x4,0 / ⚙ 0,8 Nm
type of conductor solid external	yes
type of conductor flexibel external	yes
type of conductor stranded external	yes
type of conductor solid internal	yes

**type of conductor stranded internal**      yes

---

**type of conductor flexible internal**      yes

---

## Approvals

---

**acc. to EN 60127**      [Download PDF](#)

---

**acc. to UL**      [Download PDF](#)

---

**acc. to CSA**      [Download PDF](#)

---