

# 1-Port USB 2.0 Desktop Extension Cable (M/F), 5 ft. (1.52 m)

# MODEL NUMBER: U024-005-DSK1











## **Highlights**

- Supports data transfer rates up to 480 Mbps
- Premium foil and braid shielding
- Backward compatible with earlier USB generations
- Flexible PVC jacket for easy installation in tight spaces
- Black padded non-sliding base

#### **System Requirements**

 Computer, laptop or other device with USB-A port

#### **Package Includes**

 U024-005-DSK1 1-Port USB 2.0 Hi-Speed Desktop Extension Cable (M/F), 5 ft.

Extends your desktop computer's existing USB-A port up to 5 ft. away. Ideal for connecting external hard drives, thumb drives, digital cameras and other USB-A devices.

#### **Features**

### Extends an Existing USB-A Port an Extra 5 ft.

- Move a hard-to-reach USB port within easy access
- · Ideal for connecting external hard drives, thumb drives, digital cameras and other USB-A devices
- Supports data transfer rates up to 480 Mbps
- Backward compatible with earlier USB generations

#### First-Rate Construction for Superior Signal Transfer

- Premium foil and braid shielding for EMI/RFI noise protection
- Molded nickel-plated connectors for optimal signal quality
- Integral strain relief for long life
- Flexible PVC jacket for easy installation in tight spaces
- Black padded non-sliding base

# **Specifications**

OVERVIEW	
UPC Code	037332199331
Technology	USB; USB 2.0 (High Speed)
USB Cable Type	Passive
INPUT	



Maximum Input Amps	1	
CHARGING		
Total Charging Watts	5	
PHYSICAL		
Material of Construction	PVC	
Cable Jacket Color	Black	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	3.5mm	
Cable Length (ft.)	5	
Cable Length (m)	1.52	
Unit Packaging Type	Polybag	
ENVIRONMENTAL		
Operating Temperature Range	32 to 104 F (0 to 40 C)	
Storage Temperature Range	14 to 131 F (-10 to 55 C)	
Relative Humidity	5% to 90% RH, Non-Condensing	
Operating Humidity Range	0% to 90% RH, Non-Condensing	
Storage Humidity Range	0% to 90% RH, Non-Condensing	
Power Provided to Connected Device(s)	5W (5V/1A)	
CONNECTIONS		
Side A - Connector 1	USB A (MALE)	
Side B - Connector 1	USB A (FEMALE)	
Connector Plating	Nickel	
Contact Plating	Gold	
FEATURES & SPECIFICATIONS		
USB Specification	USB 2.0 (up to 480 Mbps)	
Data Transfer Rate	480 Mbps	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; REACH	
WARRANTY & SUPPORT		



Product Warranty Period (Worldwide)	Lifetime limited warranty
-------------------------------------	---------------------------



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.