

## Specification Sheet

Part Number: 151-02291

Integrated design allows for easy insertion by hand.

1.5–2mm panel thickness range allows for multiple applications.

Double-compression design that accommodates various sizes of wire and cable.

Presents a high extraction force for withstanding extreme conditions.



Article Number 151-02291

Type MSC90

Color Metal (ML)

Quantity Per box

**Product Description**

HellermannTyton's 90-Degree Metal Edge Clip provides an excellent alternative to managing wire and PV cables where plastic fasteners are not the preferred method. Designed for effortless insertion, this edge clip also has a high extraction force. The 90-degree configuration secures cables to a panel in a perpendicular orientation. Metal construction tolerates extreme environments, and a low-profile design allows the clip to be installed on a wide variety of module edges.

**Short Description**

Low Profile 90° Metal Edge Clip, 1.5–2.0mm Panel Thickness, 6–6.2mm Cable Range, SS304, 5000/box

Global Part Name MSC90-SS304-ML

Length L (Imperial) 0.73

Length L (Metric) 18.44

Width W (Imperial) 0.460

Width W (Metric) 11.57

Bundle Diameter Min (Imperial) 0.161

Bundle Diameter Min (Metric) 4.1

Bundle Diameter Max (Imperial) 0.276

Bundle Diameter Max (Metric) 7.0

Depth D (Imperial) 0.445

Depth D (Metric) 11.303

Panel Thickness Min (Imperial) 0.06

Panel Thickness Max (Imperial) 0.078

Panel Thickness Min (Metric) 1.5

Panel Thickness Max (Metric) 2.0

Material	Stainless Steel (SS304)
Material Shortcut	SS304
Halogen Free	No
UV Resistant (Yes/No)	No
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
UL Listed (US and Canada)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	7326908695

