

Han-Port

Identification	Conductor cross-section (mm²)	Part number	
Han-Port®, Socket, With LED display, Termination at the rear, Screw termination, Germany (VDE), 62 mm / 250 V AC / 50 Hz / 16 A	6	39 50 001 0001	
Han-Port®, Socket, for assembly in front of main switch, Termination at the rear, Screw termination, Germany (VDE), 62 mm / 250 V AC / 50 Hz / 16 A	6	39 50 001 0002	
Han-Port [®] , Socket, Finger safe, Screw termination, USA, Japan, 30 mm / 125 V AC / 60 Hz / 15 A	2.5	39 50 001 0004	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Han-Port®, Socket, With LED display, Termination at the rear, Screw termination, France (UTE), 62 mm / 250 V AC / 50 Hz / 16 A	6	39 50 001 0005	
Han-Port®, Socket, Finger safe, Screw termination, Great Britain (BS), 30 mm / 250 V AC / 60 Hz, 50 Hz / 13 A	4	39 50 001 0006	75A 2007 ~
Han-Port®, Socket, Double, Finger safe, Screw termination, Italy (CEI 23-16), 20 mm / 250 V AC / 50 Hz / 16 A	2.5	39 50 001 0007	MA 2007- MA 2007-