



NEMA 5-15
SUPER-SAFEWAY
PART NO. 1447
COLOR: YELLOW

NEMA 5-15
SUPER-SAFEWAY
PART NO. 1547
COLOR: YELLOW

#12-3 STJW, 300V CORD
COLOR: YELLOW

LED INDICATOR
CONFIRMS POWER
AND FAULT STATUS

AUTOMATIC OR
MANUAL (SAFE START)
RESET TYPES

HIGH STRENGTH
POLYCARBONATE
HOUSING
COLOR: BLACK

NYLON CLAMP

RUBBER HUSK

(1.75)

(2.74)

MATERIAL NO.	ENGINEERING NO.	LENGTH "L"	LENGTH "A"	POWER-UP
1301530043	15051-1A	2 FT 7 IN	1 FT ± 1 IN	AUTO
1301530052	15051-6A	7 FT 7 IN	6 FT ± 2 IN	AUTO
1301530046	15051-25A	26 FT 7 IN	25 FT ± 2 IN	AUTO
1301530049	15051-50A	51 FT 7 IN	50 FT ± 4 IN	AUTO
1301530044	15051-1M	2 FT 7 IN	1 FT ± 1 IN	MANUAL
1301530053	15051-6M	7 FT 7 IN	6 FT ± 2 IN	MANUAL
1301530047	15051-25M	26 FT 7 IN	25 FT ± 2 IN	MANUAL
1301530050	15051-50M	51 FT 7 IN	50 FT ± 4 IN	MANUAL

TECHNICAL:
LISTED: cULus
RATED SUPPLY VOLTAGE: 120 VAC
RATED CURRENT: UP TO 15 AMPS OR CABLE RATING
RESET TYPE: AUTOMATIC OR MANUAL
OPERATING FREQUENCY: 60 Hz
TYPE: CLASS A
GROUND TRIP CURRENT: 4-6 mA
OVERLOAD CURRENT: 90 AMP 125 VAC
INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE
ENDURANCE OPERATIONS: 3000 OPERATIONS

FUNCTIONAL SYMBOLS FA = 0 FC = 0 FD = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	CURRENT REV DESC: MIGRATION TO ECTR/NX		
	DIMENSION UNITS: INCH	SCALE: NTS	EC NO: 684571	
DIVISIONAL SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRWN: VASUTHKARP 2021/11/08	PRODUCT CUSTOMER DRAWING
	ANGULAR TOL ± 0.5°		CHK'D: DNGUYEN62 2022/01/20	
	4 PLACES ±		APPR: HKNEELAND 2022/02/02	DOC TYPE: PSD
	3 PLACES ±		INITIAL REVISION:	DOC PART: 001
2 PLACES ± 0.13		DRWN: HRUIZ01 2013/02/06	REVISION: A1	
1 PLACE ± 0.25		APPR: JFMURPHY 2015/04/20	MATERIAL NUMBER: SEE TABLE	
0 PLACES ±		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	CUSTOMER: GENERAL MARKET	
THIRD ANGLE PROJECTION		DRAWING: D-SIZE	SHEET NUMBER: 1 OF 1	
		SERIES: 130153		