



RECOMMENDED LAND PATTERN DIMENSION OF PCB

- NOTES
- SMT LEAD-COPLANARITY: 0.1 MAX.
 - THIS PRODUCT HAS NO POLARITY TO PATTERN FOR MOUNTING.
 - MAKE SURE WIDTH OF PATTERN IS WITHIN THAT OF LAND, OR LEAD MAY TOUCH PATTERN. (THIS APPLIES TO HATCHED AREA.)

HRS DRAWING FOR REFERENCE

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
△					△				

CONTACT AREA: GOLD (0.1μm) OVER NICKEL		LEAD: GOLD FLASH OVER NICKEL		PHOSPHOR BRONZE		TIN PLATED		FINISH, REMARKS		APPROVED		RELEASED	
2	PHOSPHOR BRONZE	1	LCP	3	PHOSPHOR BRONZE	3	PHOSPHOR BRONZE	3	PHOSPHOR BRONZE	3	PHOSPHOR BRONZE	3	PHOSPHOR BRONZE
LEAD: GOLD FLASH OVER NICKEL		BEIGE UL94V-0		FINISH, REMARKS		MATERIAL		NO.		DESIGNED		CHECKED	
CL		CL		CL		CL		CL		CL		CL	
DRAWING NO.		EDC3-152645		PART NO.		FX11B-100S-SV		CODE NO.		CL573-0753-0		1/1	
SCALE		5 : 1		UNITS		mm		HRS		HIROSE ELECTRIC CO., LTD.		FORM NO. 229	

TO PCK