




MT20/20-CC90S-AN

Ruland T-Connector Mini-Clamp With Stud, Thru Hole 20mm, Stud Diameter 20mm, Stud Length 26mm, Black Anodized Aluminum





Description

Ruland MT20/20-CC90S-AN is a 90 degree connector with stud with a thru hole for 20mm round or 16mm square tube, 20mm stud diameter, 26mm stud length, and 51.0mm body length. It is designed to fit on Ruland tubes and flange bolt bases that begin with MT20. MT20/20-CC90S-AN is aluminum with a black anodized finish and screws are 304 stainless steel for added corrosion resistance when compared to unplated types. This 90 degree connector clamp with stud is commonly used to support tubes for mounting sensors, screens, reflectors, plexiglass machine guards, and other industrial components. The thru hole allows designers flexibility to reposition the clamp or tube as needed. The stud allows for a more compact installation than other connectors which require the use of a second tube that is significantly longer than the stud. MT20-ALK-M6-30 adjustable clamping lever can be used in place of standard clamp hardware for rapid repositioning of the tube or connector without the need for tools. MT20/20-CC90S-AN is manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Thru Hole Diameter B	20 mm	Thru Hole Tolerance	+0.13/-0 mm
Bolt Length LB	26 mm	Bolt Diameter DB	20 mm
Square Thru Hole S	16 mm	Body Length L1	51 mm
Edge To Center L2	22 mm	Screw To Edge LS	12 mm
Hole Depth T	18 mm	Width & Height W1	30 mm
Clamp Screw CL	M6	Set Screw SS	M6
Weight (lbs)	0.418900	Material Specification	Anodized Aluminum
Manufacturer	JW Winco/ Otto Ganter	UPC	634529231982
Country of Origin	Germany	Tariff Code	7609.00.0000
UNSPC	31162908		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Prop 65	▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State of California		
	to cause cancer. For more information go to www.P65Warnings.ca.gov .		