



Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 13.6 mm, Colour: Red

Business data	
Article number	27152.9
Article name	PQI 6/2 RD
GTIN (EAN)	4044211225346
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	2.94 g
Weight per piece (including packaging)	3 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	27152.9
Product description	Insulated cross-connector

Data sheet 27152.9 PQI 6/2 RD



Technical data

Dimensions	
Length	4 mm
Width	13.6 mm
Height	22.5 mm
Pitch size	8.1 mm
Ratings	
Max. voltage	800 V
Rated current	41 A
Current load, max.	41 A
Rated cross-section	6 mm²
Contamination degree	3
Connection data	
No. of poles	2
Materials	
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C
Further technical data	
Mounting type	Plug in
Insulation available	\checkmark
Touch protection is available	\checkmark
Number of bridged terminals	2
Environmental Product Compliance	
REACH Conform	yes
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet 27152.9 PQI 6/2 RD

Media



Data sheet 27152.9 PQI 6/2 RD



Accessories

##INVERSE##CONTA-CONNECT

	Three-level initiator terminal Multi-wire terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey				
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27049.6	PIKD 2,5/1PE/L/N GR	4044211227180	50 ST	
	Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm ² , Width: 8.1 mm, Colour: Green-yellow				
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27021.2	PSL 6/3A GNYE	4044211223960	50 ST	
	Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm ² , Width: 8.1 mm, Colour: Green-yellow				
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27023.2	PSL 6/4A GNYE	4044211224004	50 ST	
	Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm ² , Width: 8.1 mm, Colour: Green-yellow				
			• • • •	S 35/7.5,	
			• • • •	S 35/7.5, Packaging unit	