



## Screw Terminal Blocks

### 230/ 4

terminal block, 4 pole, insulating material: PA, cross-section rating: 2.5 mm<sup>2</sup>, pin spacing: 8.00 mm, mounting hole diameter: 2.8 mm, fixing: screw, voltage rating: 450 V, current rating: 24 A



### Order Info

reference number (ref.no.)	121204
PU	500
EAN	4028012105182

### Type

type	terminal block
number of poles	4 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm <sup>2</sup>
connection type	screw

### Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	4.0 mm <sup>2</sup>
flammability rating	V-2
min. ambient temperature	-40 °C
max. ambient temperature operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	5.0-5.5 mm
assembly contact screw	0,8x4,0 / ⚙ 0,5 Nm
mounting hole diameter	2.8 mm
pin spacing	8.00 mm
fixing	screw

## Approvals

<b>acc. to EN 60998</b>	<a href="#">Download PDF</a>
<b>acc. to UL</b>	<a href="#">Download PDF</a>
<b>acc. to CSA</b>	<a href="#">Download PDF</a>

## Accessories

<b>230 BZ/ 4</b>	191204
<b>ZEL 110</b>	196420