

Product data sheet

Specifications



Limit switch body, Limit switches XC Standard, ZCP, compact, 1NC+1 NO, slow break

ZCP25

Main

| | |
|---------------------------------|---|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard compact |
| Product or component type | Limit switch body |
| Device short name | ZCP |
| Design | Compact |
| Body type | Fixed |
| Associated head | ZCE64 ZCE62 ZCE27 ZCE28 ZCE65 ZCE11 ZCE14 ZCE10 ZCE67 ZCE06 ZCE24 ZCE29 ZCE63 ZCE01 ZCE05 ZCEH0 ZCE02 ZCE13 ZCE08 ZCE07 ZCE21 ZCEH2 ZCE66 |
| Body material | Plastic |
| Number of poles | 2 |
| Contacts type and composition | 1 NC + 1 NO |
| Contact operation | Slow-break, break before make |
| Complementary | |
| Associated connection component | ZCPEF12 ZCPEP20 ZCPEG13 ZCPEG11 ZCPEP16 ZCPEN12 |
| Electrical connection | Screw-clamp terminals, clamping capacity: 1 x 0.5...2 x 2.5 mm ² |
| Contacts insulation form | Zb |
| Contacts material | Silver plated contacts |

| | |
|--|---|
| Positive opening | With |
| Minimum actuation speed | 6 m/s |
| Contact code designation | B300, AC-15 (U _e = 240 V), I _e = 1.5 A conforming to EN/IEC 60947-5-1 appendix A R300, DC-13 (U _e = 250 V), I _e = 0.1 A conforming to EN/IEC 60947-5-1 appendix A |
| [Ui] rated insulation voltage | 300 V conforming to UL 508 500 V (pollution degree 3) conforming to IEC 60947-1 300 V conforming to CSA C22.2 No 14 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60664 6 kV conforming to IEC 60947-1 |
| Short-circuit protection | 10 A cartridge fuse, type gG |
| Electrical durability | 5000000 cycles, DC-13 120 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 13 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width | 31 mm |
| Height | 65 mm |
| Depth | 30 mm |
| Net weight | 0.07 kg |

Environment

| | |
|---------------------------------------|-------------|
| Product compatibility | XCKP |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.2 cm |
| Package 1 Width | 4.2 cm |
| Package 1 Length | 7.6 cm |
| Package 1 Weight | 61.0 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 81 |
| Package 2 Height | 15.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 5.439 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

California proposition 65

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty

18 months

Recommended replacement(s)