



Insulated cross-connector, No. of poles: 40, Mounting type: Can be screwed on, Colour: Yellow

RAL: 1026

Business data

Article number	2746.2	
Article name	QI 40 YE	
GTIN (EAN)	4044211126957	
Packaging unit	5	
Quantity unit	PC	
Weight per piece (not including packaging)	71.2 g	
Weight per piece (including packaging)	71.4 g	
Unit of weight	G	
Customs number	85389099	
Country of origin	CZ	
Product description	Insulated cross-connector	
Colour	Yellow	



Technical data		
Dimensions		
Length	2.3 mm	
Pitch size	6 mm	
Ratings		
Voltage with partition, max.	800 V	
Voltage without partition, max.	400 V	
Rated current	32 A	
Contamination degree	3	
Connection data		
No. of poles	40	
Screw head	Slotted	
Screw threading	M 3	
Tightening torque, min.	0.5 Nm	
Tightening torque, max.	1 Nm	
Materials		
Material	Copper	
Surface	Tin-plated	
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	105 °C	
Further technical data		
Mounting type	Screwable	
Insulation available	✓	
Number of bridged terminals	40	

Data sheet



2746.2 QI 40 YE

Environmental Product Compliance			
REACH Conform	No		
REACH Reference date	2023-01-17		
REACH Candidate Substance Note	No		
REACH CAS 1 Substance	LEAD		
REACH CAS 1 Percent minimal	0.1 %		
REACH CAS 1 Percent maximum	4 %		
REACH CAS 1 Number	7439-92-1		
RoHS Conform	yes		
RoHS Exception rule	6c		



Media





Accessories

Screwdriver

Screwdriver with bare blade, Colour: Black-grey



Article number	Article name	GTIN (EAN)	Packaging unit
1086.0	SDB 0,6x3,5	4044211014797	1 ST