

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE			
△				.	△				.			
△				.	△				.			
APPLICABLE STANDARD												
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +85 °C (NOTE1)			STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C						
	VOLTAGE	250 V AC			APPLICABLE CONTACT							
	CURRENT	3 A			APPLICABLE CONNECTOR							
					APPLICABLE CABLE							
SPECIFICATIONS												
ITEM	TEST METHOD				REQUIREMENTS				Q	T	A	T
CONSTRUCTION												
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				○	○		
MARKING	CONFIRMED VISUALLY.								○	○		
ELECTRICAL CHARACTERISTICS												
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).				30 mΩ MAX.				○	—		
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.	20 mV MAX. mA (DC OR 1000 Hz).				mΩ MAX.				—	—		
INSULATION RESISTANCE	500 V DC				1000 MΩ MIN.				○	—		
VOLTAGE PROOF	650 V AC FOR 1 min				NO FLASHOVER OR BREAKDOWN.				○	—		
MECHANICAL CHARACTERISTICS												
CONTACT INSERTION AND EXTRACTION FORCES	BY STEEL GAUGE.				INSERTION FORCE N MAX. EXTRACTION FORCE N MIN.				—	—		
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.				INSERTION FORCE N MAX. EXTRACTION FORCE N MIN.				—	—		
MECHANICAL OPERATION	≥ 20 TIMES INSERTIONS AND EXTRACTIONS				① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				○	—		
VIBRATION	FREQUENCY 10 TO 55 Hz. SINGLE AMPLITUDE 0.75 mm. — m/s ² AT 2 h FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF / μs. ② CONTACT RESISTANCE: — mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				○	—		
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF / μs. ② CONTACT RESISTANCE: — mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				○	—		
ENVIRONMENTAL CHARACTERISTICS												
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90~95%, 96 h.				① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 1000 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				○	—		
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → -5~35 → +85 → 5~35 °C TIME 30 → 5 → 30 → 5 min UNDER 5 CYCLES.				① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 1000 MΩ. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				○	—		
RESISTANCE TO SOLDERING HEAT	SOLDER TEMPERATURE, °C FOR IMMERSION, DURATION, s.				NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.				—	—		
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, °C FOR IMMERSION DURATION, s.				A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.				—	—		
REMARKS NOTE1 INCLUDE THE TEMPERATURE RISING BY CURRENT. Unless otherwise specified, refer to MIL-STD-1344.					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED			
					<i>R. Sasaki</i>	<i>M. Tanaka</i>	<i>J. Oma</i>	<i>H. Yamamoto</i>				
					'95.10.12	'95.10.13	'95.10.17	'95.10.23				
Note Q T: Qualification Test A T: Assurance Test ○: Applicable Test												
HRS HIROSE ELECTRIC CO., LTD.					SPECIFICATION SHEET			PART NO. DF1BA-※EP-2.5RC				
CODE NO. (OLD) CL			DRAWING NO. ELC4-160595			CODE NO. CL			CODE NO. SHALL BE IN ACCORDANCE WITH TABLE.			

TO