



Connectors System AC 164 Panel Mounting

AC 164 EBU/ 3 WS

socket, 3 pole, white, coding: 1 (mains), voltage rating: 250 V, current rating: 16 A, cross-section rating: 2.5 mm², wall thickness min.: 0.5 mm, wall thickness max.: 1.2 mm



Order Info

| | |
|-----------------------------------|---------------|
| reference number (ref.no.) | 148653 |
| PU | 200 |
| EAN | 4028012123919 |

Type

| | |
|--|---------------------|
| type | socket |
| number of poles | 3 pole |
| clamping units per pole | 1 |
| colour | white |
| coding | 1 (mains) |
| cross-section rating | 2.5 mm ² |
| connection type | screw |
| PE function | yes |
| protection against incorrect plugging | yes |
| latch | yes |

Technical Data

| | |
|---|---------------------|
| voltage rating | 250 V |
| current rating | 16 A |
| impulse voltage rating | 4.0 kV |
| insulating material | PA |
| contact material | brass |
| core cross-section min. | 0.5 mm ² |
| core cross-section max. | 2.5 mm ² |
| flammability rating | V-2 |
| max. ambient temperature operation | 70 °C |
| IP code | IP20 |
| IP code when plugged | IP40 |
| type of conductor solid | yes |
| type of conductor flexible | yes |
| type of conductor stranded | yes |

| | |
|-------------------------------|-----------------|
| stripping length | 7.0 mm |
| assembly contact screw | PZ 1 / ⚙ 0,5 Nm |
| wall thickness min. | 0.5 mm |
| wall thickness max. | 1.2 mm |

Approvals

| | |
|-------------------------|------------------------------|
| acc. to EN 61535 | Download PDF |
| acc. to UL | Download PDF |

Accessories

| | |
|-------------------------|--------|
| AC 164 VT 3/3 WS | 149753 |
|-------------------------|--------|