



Technical Specifications

Rose Batteries Standard Lithium Ion Battery 3.6V, 4300mAh

Part Number	LI-1S2P-4400
Description	3.6V 4300mAh (min capacity) lithium ion battery with a safety unit.
Cell Used	Panasonic UR18650A or equivalent
Operating Temperature	Charge temperature range: 0° to +40° C Discharge temperature range: -20° to +60° C Storage temperature range: -20° to +60° C
Operating Humidity	45% - 85% under all conditions
Voltage	Typical open circuit voltage on shipment: 3.6 V Minimum voltage on discharge: 3.0 V Maximum voltage on charge: 4.2 V
Current	Maximum charge current: 3A Maximum discharge current: 3A
Safety Unit	Nominal over-voltage cutoff: 4.325V \pm 0.025 V Nominal under-voltage cutoff: 2.500V \pm 0.080 V Nominal over-current cutoff: 3A
Date Code Labeling	Battery packs are labeled with the date of assembly – YYWW format
Storage	Batteries may be stored under the specified storage temperature range for a maximum of six months from the date of pack assembly.
Cable length	2.25" +/- .25" long
Connector	Molex 50-37-5023
Pins	Molex 08-70-1040
Weight	Nominal Weight: 110 g
Dimensions	Maximum Length: 2.66" Maximum Width: 1.45" Maximum Height: 0.80"
Warranty	1 year from date of assembly, as detailed in Rose Warranty.
Regulatory	Cells and packs passed UN 38.3; cells certified to UL 1642 and IEC 62133

Photograph

