

SPECIFICATIONS:

INPUT VOLTAGE: 120V 60Hz 6A

277V 60HZ 3A

FOR TUNGSTEN, BALLAST AND GENERAL PURPOSE LOADS

OUTPUT VOLTAGE: 120V-277V 60Hz ETL LISTED (CONFORMS TO UL STD. 508)

1, 2, 3 WIRES 18 AWG, AWM 1007 INSULATED, VW-1 FT 1 RATED REMAINING WIRES 18 AWG, AWM 1015 INSULATED, VW-1 FT 1 RATED

ALL DIMENSIONS ARE IN MM	DRAWN BY BMN		THIS DOCUMENT IS CONFIDENTIAL AND IS THE SOLE PROPERTY OF CREST ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN PERMISSION IS PROHIBITED		
TOLERANCES UNLESS SPECIFIED X ± .51 X.X ± .25 X.XX ± .13 < ±1° THIRD ANGLE PROJECTION	DATE 12/02/20		CREST ELECTRONICS'		
	APPROVED BY BMN		DESCRIPTION CONTROLLER, LOW VOLTAGE, 2 CIRCUIT		
	DATE 12/02/20		SIZE A	DWG. NO. 115229-ND	REV.
	SCALE: NTS	SHEET 1 OF 1		113229-ND	01