



# 4S-Series

Miniature Slide Switches

**PRODUCT WEBPAGE**

*request sample, configure part*



The 4S-Series sub-miniature slide switches feature maintained and momentary 2 or 3 position circuits, and offer a variety of ratings, contact materials, terminal platings, and mounting styles. These switches are able to withstand temperatures from -30°C to +85°C.

<b>1</b>	<b>.4-3</b>	<b>125, 250</b>	<b>28</b>
Pole	Amps	VAC	VDC

## Typical Applications

- Consumer Electronics
- Instrumentation
- Computer Servers / Peripherals
- Test / Measurement

# Tech Specs

## Electrical

Contact Rating	refer to ordering scheme
Electrical Life	30,000 make & break cycles @ full load
Contact Resistance	10 mΩ max. initial @ 2-4 VDC 100mA for both silver & gold plated contacts
Insulation Resistance	1000 MΩ min.
Dielectric Strength	1500 Volts RMS @ sea level

## Physical

Operating Temperature	-30°C to +85°C
Solder Heat Resistance	MIL-STD-202, Method 210

## Material

Case	Dially phthalate (DAP) (UL 94V-0)
Slide Handle	Nylon
Housing	Stainless Steel
Terminal Seal	Epoxy

# Ordering Scheme

Sample Part Number **4S1 - FSP 1 - M6 Q E T/R**

Selection 1 2 3 4 5 6 7

### 1. SERIES

**4M1** Miniature Slide Switch

### 2. POLES

**FSP** Single Pole

### 3. CIRCUIT

( ) - momentary

Position:	1	2	3
	2-1	Connected Terminals	2-3
1	ON	NONE	ON
2	ON	NONE	(ON)
3	ON	OFF	ON

### 4. TERMINATION

**M2** PCB  
**M6** PC Mount, horizontal, right angle  
**M7** PC Mount, vertical, right angle  
**M7I** Snap-In, vertical, right angle

### 5. CONTACTS / TERMINALS

Contact Material	Terminal Plating	Rating
<b>G</b> silver <sup>1</sup>	gold over silver	3A 125VAC or 28VDC; 1.5A 250VAC
<b>K</b> gold <sup>2,5</sup>	tin <sup>4,7</sup>	0.4VA max 20V max (AC/DC)
<b>P</b> silver <sup>1,6</sup>	tin <sup>4,7</sup>	3A 125VAC or 28VDC; 1.5A 250VAC
<b>Q</b> silver <sup>1</sup>	silver <sup>1</sup>	3A 125VAC or 28VDC; 1.5A 250VAC
<b>R</b> gold <sup>2</sup>	gold <sup>3</sup>	0.4VA max 20V max (AC/DC)

### 6. EPOXY SEAL

**E** Epoxy Seal **0** without Epoxy Seal

### 7. PACKAGING

**T/R** tape reel - 500 pieces per reel  
 Switches are bulk packed, unless T/R is specified at the end of the part number.

#### Notes:

- Movable contact / terminal platings: silver over copper alloy
- Movable contact platings: gold over nickel over copper alloy
- Terminal platings: gold over nickel over copper alloy
- Terminal platings: tin over copper alloy, available with PC type terminations only
- Terminal contact platings: gold over nickel alloy
- Terminal contact platings: silver over nickel alloy
- Tin option available with PC type terminations only




[Configure Complete Part Number >](#)

[Browse Standard Parts >](#)

# Dimensional Specs

inches [millimeters]




## M2 Single Pole




## P.C.MOUNTING



## M6 Single Pole






## P.C.MOUNTING




## M7 Single Pole

## M71 Snap-In Termination Single Pole



## P.C.MOUNTING



## Authorized Sales Representatives and Distributors

Click on a region of the map below to find your local representatives and distributors or visit [www.carlingtech.com/findarep](http://www.carlingtech.com/findarep).



## About Carling

Founded in 1920, Carling Technologies is a leading manufacturer of electrical and electronic switches and assemblies, circuit breakers, electronic controls, power distribution units, and multiplexed power distribution systems. With six ISO9001 and IATF16949 registered manufacturing facilities and technical sales offices worldwide, Carling Technologies Sales, Service and Engineering teams do much more than manufacture electrical components, they engineer powerful solutions! To learn more about Carling please visit [www.carlingtech.com/company-profile](http://www.carlingtech.com/company-profile).

To view all of Carling's environmental, quality, health & safety certifications please visit [www.carlingtech.com/environmental-certifications](http://www.carlingtech.com/environmental-certifications).

© Carling Technologies, Inc.

4. Carling is a registered trademark of Carling Technologies, Inc. in the U.S. and other countries.