

Desktop Computer AC Power Cable, NEMA 5-15P to C13 - 10A, 125V, 18 AWG, 4 ft. (1.22 m), Yellow Plugs

MODEL NUMBER: P006-004-YW









Computer power cable allows you to connect your PC, printer or monitor into a surge protector, PDU or UPS with a NEMA 5-15R outlet.

Features

Desktop Computer Power Cord Connects PCs, Printers, Monitors and Other EquipmentThis computer power supply cable is designed for home/office desktop computer applications. You can use it to connect a computer, monitor, printer, scanner or other device with a C14 power inlet to an AC wall outlet, surge protector, UPS system or PDU. The 4-ft. (1.22 m) length helps reduce cable clutter and minimize the risk of tripping.

Color-Coded to Avoid Misidentification That Can Cause Costly DowntimeThis computer AC power cable features fully molded yellow ends. The color-coding allows easy, fast identification in a crowded rack or workstation and helps prevent the cable from becoming inadvertently disconnected.

Highlights

- Recommended for powering computers, printers and other home/office peripherals
- 4-ft. (1.22 m) length allows flexibility in placing devices, while avoiding cable clutter
- NEMA 5-15P to C13 extension cord is ideal replacement for worn-out or missing cable
- Yellow plugs for fast, easy identification in a crowded PDU, UPS or surge protector

Applications

- Connect devices like computers, printers and monitors to a PDU up to 4-ft. (1.22 m) away in your workstation
- Extend an existing power connection up to 4-ft. (1.22 m) to more easily place a device or reach a power source
- Provide a high-quality replacement for a worn-out or missing power cord

Package Includes

 P006-004-YW NEMA 5-15P to C13 Computer Power Cable, 4ft. (1.22 m), Yellow Plugs

Specifications

OVERVIEW		
UPC Code	037332168498	
Device Compatibility	Computer; Monitor/HDTV; Printer; Server; UPS; PDU	
Country/Region	North America	
INPUT		
Maximum Input Amps	10	
Voltage Compatibility (VAC)	125	
PHYSICAL		



Plug Color			
Cable Jacket Material PVC Cable Jacket Rating FT2 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 7.7mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (th) 4 Cable Length (m) 1.22 Shipping Dimensions (twd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (twd / in.) 25.40 x 18.03 x 1.27 Shipping Weight (fbs.) 0.37 Shipping Weight (kg) 0.17 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (-20* TO 60*C) Operating Temperature Range -4 TO 140 F (-20* TO 60*C) Operating Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No Locking Plug No WARRANTY & SUPPORT	Plug Color	Yellow	
Cable Jacket Rating	Cable Jacket Color	Black	
Power Cord Jacket Type	Cable Jacket Material	PVC	
Cable Outer Diameter (OD) 7.7mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (ft.) 4 Cable Length (m) 1.22 Shipping Dimensions (hwd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (lbs.) 0.37 Shipping Weight (kg) 0.17 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (-20° TO 60°C) Storage Temperature Range -4 TO 140 F (-20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Cable Jacket Rating	FT2	
Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (tt.) 4 Cable Length (m) 1.22 Shipping Dimensions (hwd / rm) 10.00 x 7.10 x 0.50 Shipping Dimensions (hwd / rm) 25.40 x 18.03 x 1.27 Shipping Weight (lbs.) 0.37 Shipping Weight (kg) 0.17 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No Locking Plug No WARRANTY & SUPPORT	Power Cord Jacket Type	SJT	
Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (ft.) 4 Cable Length (m) 1.22 Shipping Dimensions (hwd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (fwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (lbs.) 0.37 Shipping Weight (kg) 0.17 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (-20° TO 60°C) Storage Temperature Range -4 TO 140 F (-20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS NEMA 5-15P Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Cable Outer Diameter (OD)	7.7mm	
Wire Gauge (OD - mm²) 0.82 Cable Length (ft.) 4 Cable Length (m) 1.22 Shipping Dimensions (hwd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (lbs.) 0.37 Shipping Weight (kg) 0.17 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (-20° TO 60°C) Storage Temperature Range -4 TO 140 F (-20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Number of Conductors	3	
Cable Length (ft.) 4 Cable Length (m) 1.22 Shipping Dimensions (hwd / in.) 10.00 x 7.10 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (lbs.) 0.37 Shipping Weight (kg) 0.17 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Wire Gauge (AWG)	18	
Cable Length (m)	Wire Gauge (OD - mm²)	0.82	
Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (lbs.) 0.37 Shipping Weight (kg) 0.17 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No WARRANTY & SUPPORT	Cable Length (ft.)	4	
Shipping Dimensions (hwd / cm) 25.40 x 18.03 x 1.27 Shipping Weight (lbs.) 0.37 Shipping Weight (kg) 0.17 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No WARRANTY & SUPPORT	Cable Length (m)	1.22	
Shipping Weight (lbs.) Shipping Weight (kg) 0.17 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No WARRANTY & SUPPORT	Shipping Dimensions (hwd / in.)	10.00 x 7.10 x 0.50	
Shipping Weight (kg) ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Shipping Dimensions (hwd / cm)	25.40 x 18.03 x 1.27	
ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Shipping Weight (lbs.)	0.37	
Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Shipping Weight (kg)	0.17	
Storage Temperature Range -4 TO 140 F (-20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	ENVIRONMENTAL		
Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Operating Temperature Range	-4 TO 140 F (- 20° TO 60°C)	
Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Storage Temperature Range	-4 TO 140 F (- 20° TO 60°C)	
CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Operating Humidity Range	20-80% RH	
Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Storage Humidity Range	20-80% RH	
Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	CONNECTIONS		
FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT	Side A - Connector 1	NEMA 5-15P	
Angled Plug No High Voltage No Locking Plug No WARRANTY & SUPPORT Product Warranty Period	Side B - Connector 1	IEC-320-C13	
High Voltage No Locking Plug No WARRANTY & SUPPORT Drawled Marrante Period	FEATURES & SPECIFICATIONS		
Locking Plug No WARRANTY & SUPPORT Drawled Warranty Period	Angled Plug	No	
WARRANTY & SUPPORT	High Voltage	No	
Due direct Wearrants Charles d	Locking Plug	No	
Product Warranty Period	WARRANTY & SUPPORT		
(Worldwide) Lifetime limited warranty	Product Warranty Period (Worldwide)	Lifetime limited warranty	







© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.