

# Product data sheet

Specifications



## 9007, limit switch 600 V 10amp c special +opti

9007C66B2S20

### Main

Range of product	9007
Series name	Heavy duty
Device short name	C
Head type	Turret head rotary lever
Type of operator	spring return lever arm (first stage : 10° - second stage : 2.5°) (to be ordered separately) spring return lever arm (standard pre-travel)
Switch actuation	CW and CCW
Cable entry	NPT conduit entry, cable outer diameter: 12.70 mm
Contacts type and composition	2 NO/2 NC
Contact operation	Snap action Two stage

### Complementary

Body material	Zinc alloy
Switch function	SPDT-DB
Contact form	Form Z
Contacts material	Silver alloy (Ag/Ni)
Minimum torque for tripping	0.45 N.m
Tripping angle	4 °
Maximum displacement angle	90 °
[Ie] rated operational current	10 A, A600 10 A, R300
[Ui] rated insulation voltage	600 V
Product certifications	UL listed CE CSA
Provided equipment	Receptacle

### Environment

Ambient air temperature for operation	-29...85 °C
---------------------------------------	-------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.3 cm
Package 1 Width	6.9 cm
Package 1 Length	10.7 cm
Package 1 Weight	571.5 g

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Recommended replacement(s)