

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	OPERATING & STORAGE HUMIDITY RANGE	85%MAX	VOLTAGE	AC 125V	
			CURRENT	0.5 A	
<b>SPECIFICATIONS</b>					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
<b>CONSTRUCTION</b>					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
<b>ELECTRICAL CHARACTERISTICS</b>					
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	65 mΩ MAX. (SIGNAL) <span style="border: 1px solid black; padding: 0 2px;">1</span>	X	X	
INSULATION RESISTANCE	100 V DC.	1000 MΩ MIN.	X	—	
VOLTAGE PROOF	250 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	X	
<b>MECHANICAL CHARACTERISTICS</b>					
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE 25N MAX. WITHDRAWAL FORCE 2.6 N MIN.	X	—	
MECHANICAL OPERATION	1000 TIMES INSERTIONS AND EXTRACTIONS.	1) CONTACT RESISTANCE 85 mΩ MAX. <span style="border: 1px solid black; padding: 0 2px;">1</span> 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
VIBRATION	FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES.	1) NO ELECTRICAL DISCONTINUITY OF 10 μs. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
SHOCK	490 m/s <sup>2</sup> DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X	—	
<b>ENVIRONMENTAL CHARACTERISTICS</b>					
THERMAL SHOCK	TEMP -55 →+5 TO +35 →+85 →+5 TO +35 °C TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.	1) CONTACT RESISTANCE: 85 mΩ MAX. <span style="border: 1px solid black; padding: 0 2px;">1</span> 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
HUMIDITY LIFE	TEMPERATURE 40 °C, HUMIDITY 90 TO 95 %, FOR 96 h	1) INSULATION RESISTANCE: 100 MΩ MIN. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
CORROSION SALT MIST	EXPOSED AT 5 % SALT WATER, FOR 48 h.	NO HEAVY CORROSION THAT LOSE FUNCTION.	X	—	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
<span style="border: 1px solid black; padding: 0 2px;">A</span>					
REMARK		APPROVED	A0. SUZUKI	10.10.06	
<span style="border: 1px solid black; padding: 0 2px;">1</span> EXCLUDES CONDUCTOR RESISTANCE OF CABLE.		CHECKED	YH. ENAMI	10.10.06	
2 EXAMINATION IS HELD WITH "DH-17-CV * B", "DH40-17S" AND "DH60-17P" OR "DH-17-CT * B", "DH40-17S" AND "DH60A-17P".		DESIGNED	YH. MAMADA	10.10.01	
Unless otherwise specified, refer to JIS C 5402 .		DRAWN	YH. MAMADA	10.10.01	
Note	QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-127106-00		
<b>HRS</b>	SPECIFICATION SHEET	PART NO.	DH40-17S		
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0054-0-00	<span style="border: 1px solid black; padding: 0 2px;">A</span>	1/1