



Three-wire installation terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 5.1 mm, Colour: Beige

Business data	
Article number	<u>3283.2</u>
Article name	FDLI 2,5-4 NT/L/PE
GTIN (EAN)	4044211181604
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	26 g
Weight per piece (including packaging)	27.25 g
Unit of weight	G
Customs number	85369010
Country of origin	BG
Product description	Three-wire installation terminals
Colour	Beige



Technical data

Dimensions	
Length	101 mm
Width	5.1 mm
Height TS 35/7.5	55.6 mm
Ratings	
Rated voltage	400 V
Rated current	18 A
Current load, max.	32 A
Rated cross-section	4 mm²
Rated impulse voltage	6 kV
Overvoltage category	III
Contamination degree	3
Maximum power dissipation for nominal condition	1.15 W
Connection data	
Connection principle	Push-in connection
Connection position	Top/slanted
Connections	5 / hinged lever
Number of potentials	3
Wire cross-section single-core (rigid) / stranded, min.	0.2 mm ²
Wire cross-section single core (rigid)/stranded, max.	4 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	4 mm²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Wire cross-section AWG, min.	26
Wire cross-section AWG, max.	10
Stripping length	12 mm
N-function possible	\checkmark
PE function is possible	\checkmark
N partition slides available	\checkmark



Technical data

Materials		
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-0	
Working temperature, min.	-40 °C	
Working temperature, max.	120 °C	
Further technical data		
Mounting type	Mounting rail TS 35/7,5	
Gauge plug acc. to EN 60 947-1	A3	
Number of cross-connection channels	2	
End plate required	\checkmark	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-01-17	
REACH Candidate Substance Note	No	
RoHS Conform	yes	



Approvals

Standards and regulations			
EAC approval	TR ZU 004/2011		
EAC approval granted	yes		



Media





Accessories

End plate

End plate, Width: 3.5 mm, Colour: Beige			
Article number	Article name	GTIN (EAN)	Packaging unit
3487.2	FAPDT 4 BG	4044211181673	20 ST

End stop

	End stop, Mour Beige	End stop, Mounting type: Mounting rail TS 35/7.5 and TS 35/15, Width: 6 mm, Colour: Beige		
	Article number	Article name	GTIN (EAN)	Packaging unit
	3748.2	ZES 35 BG	4044211060572	50

Insulated cross-connector

Insulated cross	lated cross-connector, No. of poles: 50, Mounting type: Plug in, Colour: Yellow			
 Article number	Article name	GTIN (EAN)	Packaging unit	
3491.8	FQI 2,5-4/50 YE	4044211179496	5 ST	
Insulated cross Colour: Yellow	s-connector, No. of poles: 2, Moun	ting type: Plug in, Width: 10	0.1 mm,	
Article number	Article name	GTIN (EAN)	Packaging unit	
3492.8	FQI 2,5-4/2 YE	4044211132149	50 ST	
Insulated cross Colour: Yellow	s-connector, No. of poles: 8, Moun	ting type: Plug in, Width: 40	0.7 mm,	
			Packaging	
Article number	Article name	GTIN (EAN)	unit	



Insulated cross-connector

Insulated cross-connector, No. of poles: 9, Mounting type: Plug in, Width: 45.8 mm, Colour: Yellow

Article number	Article name	GTIN (EAN)	Packaging unit
3499.8	FQI 2,5-4/9 YE	4044211132200	10 ST
Insulated cross Colour: Yellow	s-connector, No. of poles: 10,	Mounting type: Plug in, Width	n: 50.9 mm,
Article number	Article name	GTIN (EAN)	Packaging unit
3490.8	FQI 2,5-4/10 YE	4044211132217	10 ST
Insulated cross Colour: Yellow	s-connector, No. of poles: 3, N	Nounting type: Plug in, Width:	15.2 mm,
Article number	Article name	GTIN (EAN)	Packaging unit
3493.8	FQI 2,5-4/3 YE	4044211132156	50 ST
Insulated cross Colour: Yellow Article number			Packaging
Colour: Yellow	· · · · · · · · · · · · · · · · · · ·	Nounting type: Plug in, Width: GTIN (EAN) 4044211132163	
Colour: Yellow Article number <u>3494.8</u>	Article name FQI 2,5-4/4 YE s-connector, No. of poles: 7, N	GTIN (EAN) 4044211132163	Packaging unit 20 ST 35.6 mm,
Colour: Yellow Article number 3494.8 Insulated cross Colour: Yellow	Article name FQI 2,5-4/4 YE s-connector, No. of poles: 7, N	GTIN (EAN) 4044211132163 Aounting type: Plug in, Width:	Packaging unit 20 ST 35.6 mm, Packaging
Colour: Yellow Article number <u>3494.8</u> Insulated cross Colour: Yellow Article number <u>3497.8</u>	Article name FQI 2,5-4/4 YE s-connector, No. of poles: 7, N Article name FQI 2,5-4/7 YE s-connector, No. of poles: 6, N	GTIN (EAN) 4044211132163 Aounting type: Plug in, Width: GTIN (EAN) 4044211132224	Packaging unit 20 ST 35.6 mm, Packaging unit 20 ST
Colour: Yellow Article number <u>3494.8</u> Insulated cross Colour: Yellow Article number <u>3497.8</u> Insulated cross	Article name FQI 2,5-4/4 YE s-connector, No. of poles: 7, N Article name FQI 2,5-4/7 YE s-connector, No. of poles: 6, N	GTIN (EAN) 4044211132163 Aounting type: Plug in, Width: GTIN (EAN) 4044211132224	Packaging unit 20 ST 35.6 mm, Packaging unit 20 ST



Insulated cross-connector



Insulated cross-connector, No. of poles: 5, Mounting type: Plug in, Width: 25.4 mm, Colour: Yellow

Article number	Article name	GTIN (EAN)	Packaging unit
3495.8	FQI 2,5-4/5 YE	4044211132170	20 ST

Quick marking

	Terminal marke	er / Pocket Maxicard, Length: 5 mm, Widt	h: 5 mm, Colour: White	
	Article number	Article name	GTIN (EAN)	Packaging unit
	4600.7	PMC SB 5/50 WH	4044211088903	500 ST

Screwdriver

Screwdriver with bare blade, Colour:

CONTACLIP DOTAG	Article number	Article name	GTIN (EAN)	Packaging unit
	<u>3164.0</u>	SDB 0,4x2,0	4044211107246	1 ST