

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	① -55 °C TO 85°C	STORAGE TEMPERATURE RANGE	② -55 °C TO 85 °C	
	VOLTAGE	- V	OPERATING HUMIDITY RANGE	- % TO - %	
	CURRENT	- A	APPLICABLE CABLE	-	
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.			X	X
MECHANICAL CHARACTERISTICS					
VIBRATION	FREQUENCY 10 TO 500 Hz SINGLE AMPLITUDE 0.75 mm, AT 3 TIMES FOR 3 DIRECTIONS.		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
SHOCK	490 m/s <sup>2</sup> DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 6 DIRECTIONS.			X	-
ENVIRONMENTAL CHARACTERISTICS					
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -40 → 5~35 → 105 → 5~35 °C TIME 30 → 2~ 3 → 30 → 2~ 3min. UNDER 10 CYCLES.		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.		NO HEAVY CORROSION.	X	-
<p>① THE PRODUCT PERFORMANCE IS GUARANTEED ONLY IN THE TEMPERATURE ADEQUATE TO PEOPLE'S ACTIVITIES.</p> <p>② THE OPERATION TEMPERATURE INCLUDES THE RISE BY CURRENT CARRYING.</p> <p>③ PACKING MATERIAL IS NOT INCLUDED.</p>					
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
④					
REMARK			APPROVED	YH. ENAMI	08. 11. 07
			CHECKED	HO. MIWA	08. 11. 07
			DESIGNED	YH. MAMADA	08. 11. 06
Unless otherwise specified, refer to JIS C 5402.			DRAWN	YH. MAMADA	08. 11. 06
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-044566-01
<b>HRS</b>	SPECIFICATION SHEET		PART NO.	FI-20-CV2 (50)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL230-0504-2-50	△ 1/1