


Harting Grey Plastic Cable Seals



Material
Seal
Protection
(DIN 40050)
Operating
temperature

Polyamide self-extinguishing
Buna-N
IP 68 - 10 bar (150 PSIG)
within the specified clamping range
static -40° C to 100° C, (-40° F to 212° F),
short time exposure 120° C (248° F)
dynamic -20° C to 80° C, (-4° F to 176° F),
short time exposure 100° C (212° F)

<i>Part Number</i>	<i>AG PG</i>	<i>Cable dia. mm</i>	<i>GL mm</i>	<i>H mm</i>
73 04 000 0030	7	3 – 6.5	8	20
73 04 000 0031	7	2 – 5	8	20
73 04 000 0032	9	4 – 8	8	22
73 04 000 0033	9	2 – 6	8	22
73 04 000 0034	11	5 – 10	8	24
73 04 000 0035	11	3 – 7	8	24
73 04 000 0036	13.5	6 – 12	9	27
73 04 000 0037	13.5	5 – 9	9	27
73 04 000 0038	16	10 – 14	10	28
73 04 000 0039	16	7 – 12	10	28
73 04 000 0040	21	13 – 18	11	30
73 04 000 0041	21	9 – 16	11	30
73 04 000 0042	29	18 – 25	11	38
73 04 000 0043	29	13 – 20	11	38
73 04 000 0044	36	22 – 32	13	45
73 04 000 0045	36	20 – 26	13	45
73 04 000 0046	42	32 – 38	13	47
73 04 000 0047	42	25 – 31	13	47
73 04 000 0048	48	37 – 44	14	47
73 04 000 0049	48	29 – 35	14	47
73 04 000 0022 black	21	9 – 16	11	30

