




UDSK14-11MM-8MM-F

Ruland UDSK14-11MM-8MM-F, 11mm x 8mm Double Universal Joint, Friction Bearing, Steel, Set Screw With Keyway, 22.1mm OD, 111.1mm Length





Description

Ruland UDSK14-11MM-8MM-F is a double cardan friction bearing universal joint with 11mm x 8mm bores, 4mm x 2mm keyways, 22.1mm OD, 111.1mm length, and #10-32 set screws. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UDSK14-11MM-8MM-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT14/22-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

- 1								-							-				
- 1	וע	rc		ч	ш	0		S	n		\sim	18	•	•	18	п	$\boldsymbol{\cap}$	n	
- 1		·	"	a	u	•	L	u	u	C	·		ıv	•0	ıL	•	u	•	. 3

Bore (B1)	11 mm	Small Bore (B2)	8 mm				
Keyway (K1)	4 mm	Keyway (K2)	2 mm				
B1 Max Shaft Penetration	26.2 mm	B2 Max Shaft Penetration	26.2 mm				
Joint Outer Diameter (OD)	22.1 mm	Bore Tolerance	+0.025 mm / -0.000 mm				
Length (L)	111.1 mm	Center Yoke Length (LC)	34.9 mm				
Yoke Length (LY)	38.1 mm	Hub Depth (LH)	26.2 mm				
Broached Set Screw	#10-32	Screw Finish	Black Oxide				
Peak Torque	178.0 Nm	Rated Torque	35.6 Nm				
Max Operating Angle	90°	Material Specification	Alloy Steel				
Manufacturer	Belden Universal	Country of Origin	USA				
Recommended Lubricant	LUBRIPLATE No. 1200-2	Matching Boot Cover	UBOOT14/22-NI-KIT				
UPC	63452932357	Tariff Code	8483.60.4000				
UNSPC	25173810						
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.						
Prop 65	•	expose you to the chemical Ethylene irth defects or other reproductive had	•				