



TR-822

SATA RAID 2 Ports Low Profile PCI Host Adapter

Low Profile PCI 1.5Gbps Native SATA internal 2Ports with RAID 0, RAID 1 support!

FEATURES

- Independent internal two ports high speed Native Serial ATA
- Serial ATA data rates 1.5Gbps
- 48 bits LBA can Break Capacity-Limit to Support HDD larger than 137GB
- Fully compliant with Serial ATA 1.0a specifications
- Supports Spread Spectrum in receiver
- Independent 256-byte FIFOs (32 bit * 64 deep) per Serial ATA channel for host reads and writes
- Compliant with PCI Specification, revision 2.3 Integrated PCI DMA engines
- 32 bit, 66MHz fully compliant PCI host interface
- Low Profile PCI form factor
- Includes Low profile PCI and Regular size PCI two Brackets
- Two LED Pin headers on board for HDD LED connection
- Jumper to enable / disable on board SATA BIOS
- Provides RAID 0 (Striping) to greatly increase the performance of data transfer by simultaneously reading data from 2 drives
- Provides RAID 1 (Mirroring) to protect the data from a disk failure by writing identical data on 2 drives
- Acts as NON-RAID card when BIOS not configured to RAID mode
- Completely with drivers for 64bit / 32bit Windows 7, Vista, 2000, 2003 server, XP
- Linux 32bit / 64bit drivers support for Fedora Core3, Fedora Core4, RHEL 4.0, RHEL 4.0 Up1, SuSE 9.0 SP1 RC5, SuSE Pro 9.2, SuSE Pro 9.3.
- Fully RoHS compliant Chipset : Sil3512

SPECIFICATION

- Bus Architecture: Low Profile 32bit PCI Bus (MD1)
- Dimension: 120mm x 64mm
- PCB: 4 Layers / FR-4 94V0 / 0.5 oz / 1.6mm
- SATA Ports: 2 Serial ATA Ports
- Temperature: Operating +5 °C to +50 °C Non Operating -25 °C to +70 °C
- Humidity: Operating 20% to 80% Non Operating 15% to 90%
- EMC Compliance: EN55022/1998, EN55024/1998 (*European Community*) FCC Part 15 Class B (DoC) (*US*)
- SATA Connector: S1 – GND, S2 – A+, S3 – A-, S4 – GND, S5 – B-, S6 – B+, S7 – GND
- Chipset: Silicon Image Sil3512
- Power Consumption: 5V / 470mA