

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

| COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE | COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE |
|---|-----------------------------|---|------|---------------------|--|--------------------------|------------------|----------|------|
| △ 2 | RE-F-09653 | K.N | H.Y | 04.04.06 | △ | | | | |
| △ 1 | RE-F-10251 | K.D | H.O | 05.02.02 | △ | | | | |
| APPLICABLE STANDARD | | | | | | | | | |
| RATING | OPERATING TEMPERATURE RANGE | -55 °C TO 85 °C | | | STORAGE TEMPERATURE RANGE | -10 °C TO 60 °C | | | |
| | VOLTAGE | 100 V AC | | | OPERATING HUMIDITY RANGE | 40 % TO 80 % | | | |
| | CURRENT | 0.4 A | | | STORAGE HUMIDITY RANGE | 40 % TO 70 % | | | |
| SPECIFICATIONS | | | | | | | | | |
| ITEM | | TEST METHOD | | | REQUIREMENTS | | | QT | AT |
| CONSTRUCTION | | | | | | | | | |
| GENERAL EXAMINATION | | VISUALLY AND BY MEASURING INSTRUMENT. | | | ACCORDING TO DRAWING. | | | × | × |
| MARKING | | CONFIRMED VISUALLY. | | | | | | × | × |
| ELECTRIC CHARACTERISTICS | | | | | | | | | |
| CONTACT RESISTANCE | | 100 mA (DC OR 1000 Hz). | | | 80 mΩ MAX. (1) | | | × | |
| CONTACT RESISTANCE MILLIVOLT LEVEL METHOD | | 20 mV MAX, 1 mA(DC OR 1000Hz) | | | 100 mΩ MAX. (2) | | | × | |
| INSULATION RESISTANCE | | 250 V DC. | | | 100 MΩ MIN. | | | × | |
| VOLTAGE PROOF | | 300 V AC FOR 1 min. | | | NO FLASHOVER OR BREAKDOWN. | | | × | |
| MECHANICAL CHARACTERISTICS | | | | | | | | | |
| MECHANICAL OPERATION | | 50 TIMES INSERTIONS AND EXTRACTIONS. | | | ① CONTACT RESISTANCE: 100 mΩ MAX. (2) ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | | | × | |
| VIBRATION | | FREQUENCY 10 TO 55 Hz, AMPLITUDE : 1.5 mm, AT 2 h FOR 3 DIRECTION. | | | ① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② CONTACT RESISTANCE: 100 mΩ MAX. (2) | | | × | |
| SHOCK | | 490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. | | | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | | | × | |
| ENVIRONMENTAL CHARACTERISTICS | | | | | | | | | |
| DAMP HEAT (STEADY STATE) | | EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h. | | | ① CONTACT RESISTANCE: 100 mΩ MAX. (2) ② INSULATION RESISTANCE: 100 MΩ MIN. | | | × | |
| RAPID CHANGE OF TEMPERATURE | | TEMPERATURE-55→+15~+35→+85→+15~+35°C TIME 30 → 2~3 → 30 → 2~3 min UNDER 5 CYCLES. | | | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | | | × | |
| CORROSION SALT MIST | | EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h. | | | ① CONTACT RESISTANCE: 100 mΩ MAX. (2) ② NO HEAVY CORROSION. | | | × | |
| HYDROGEN SULPHIDE | | EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA-38) | | | | | | × | |
| RESISTANCE TO SOLDERING HEAT | | 1) REFLOW SOLDERING : 250 °C MAX, : 220 °C MIN, FOR 60 s 2) SOLDERING IRONS : 360 °C, △ FOR 5 s | | | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. | | | × | |
| SOLDERABILITY △ △ | | SOLDERED AT SOLDER TEMPERATURE, 240 ± 3°C, FOR IMMERSION DURATION, 3 s. | | | A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed. | | | × | |
| REMARKS (1) THIS CONNECTOR'S INITIAL CONTACT RESISTANCE SHALL BE 80 mΩ, BECAUSE OF THE BULK RESISTANCE OF STACKING HEIGHT 16 mm TYPE. (2) AFTER TEST, THE CHANCE OF THE CONTACT RESISTANCE SHALL BE 20 mΩ MAX. | | | | | | | | | |
| | | | | DRAWN | DESIGNED | CHECKED | APPROVED | RELEASED | |
| | | | | S.SUZUKI | K.NAKAMURA | H.OKAWA | Y.YOSHIMURA | | |
| Unless otherwise specified, refer to JIS C 5402. | | | | 03.02.13 | 03.02.13 | 03.02.14 | 03.02.15 | | |
| Note QT:Qualification Test AT:Assurance Test ×:Applicable Test | | | | | | | | | |
| HRS HIROSE ELECTRIC CO., LTD. | | | | SPECIFICATION SHEET | | | PART NO. | | |
| | | | | | | | FX8C-※※P-SV6(92) | | |
| CODE NO.(OLD) | | DRAWING NO. | | | CODE NO. | | | | |
| CL | | ELC4 - 151090- 22 | | | CL 578 | | | | |
| | | | | | 1 1 | | | | |