TRIPP-LITE

USB 2.0 Ethernet NIC Adapter - 10/100 Mbps, RJ45, Black

MODEL NUMBER: U236-000-R



Connects your USB-enabled computer or laptop to a 10/100 Mbps Ethernet network without installing an internal Ethernet card.

Features

Connects Your USB Device to a Wired Ethernet Network without an Internet Card InstalledThis USB to Ethernet adapter allows you to instantly connect your computer, laptop, tablet or other USB-compatible device to a wired 10/100 Mbps Ethernet network, even if your device has no NIC (Network Interface Controller) installed. The adapter is a more convenient, less expensive way to go online than opening your device and installing an internal Ethernet card.

Plug and Play with No Power Supply NeededThis USB 2.0 Ethernet adapter offers access to an Ethernet network when Wi-Fi is unavailable or when a wired connection offers faster speeds. Just connect the built-in USB cable to your device's USB port (which also powers the adapter), and wait for the installation process to finish (you may have to reboot your computer). Then, connect the RJ45 port to a LAN port using a Cat5e/6 network cable (such as Tripp Lite's N201-Series Cat6 UTP patch cable, sold separately). The adapter works with Windows, Mac and Linux operating systems. It is backward compatible with USB 1.1 devices.

Delivers Full Ethernet PerformanceThe compact USB to Ethernet adapter supports full 10/100 Mbps network speeds and USB 2.0 speeds, allowing you to transfer data quickly and stream audio and video. It's compliant with IEEE 802.3, 802.3u, 802.3ab and 802.3az standards. It supports full duplex with IEEE 802.3x flow control and half duplex with backpressure flow control. LEDs indicate successful data transfers.

Specifications

OVERVIEW	
UPC Code	037332163127
Technology	Cat5/5e; Cat6; USB 2.0 (High Speed)
INPUT	

Highlights

- Connects you to a wired Ethernet network when Wi-Fi is weak or unavailable
- Supports USB 2.0 speeds to ensure efficient data transfers
- Sustains full 10/100 Mbps network speeds for fast Ethernet browsing
- Works with most laptops and PCs running Windows, Mac or Linux
- USB 2.0 Ethernet adapter powered via USB, so no external power supply is required

Applications

- Upload data from your notebook or download data from the Ethernet at true 10/100 Mbps speeds
- Replace a malfunctioning RJ45 port or Ethernet card on your laptop or PC

System Requirements

- IBM-compatible Pentium PC or Mac with 233 MHz or faster
- 64 MB RAM or more
- Computer or laptop with USB port
- Windows (through 10), Mac (through 10.10/10.11) or Linux Kernel (2.6.14 and later) OS

Package Includes

- U236-000-R USB 2.0 Ethernet NIC Adapter
- Driver CD
- Quick Start Guide

TRIPP-LITE

Power Power Consumption (Watts) 0.75 PhysicAL Color Black Material of Construction ABS, PVC Color Black Material of Construction ABS, PVC Color 0.50 x 5.20 x 5.30 Shipping Dimensions (hvd /in.) 0.50 x 5.20 x 5.30 Shipping Dimensions (hvd /in.) 0.50 x 5.20 x 5.30 Shipping Ximage (http://www.comstruction) ABS, PVC Uhit Dimensions (hvd /in.) 0.50 x 5.20 x 5.30 Shipping Ximage (http://www.comstruction) Shipping Ximage (http://www.comstruction) Uhit Dimensions (hvd /in.) 0.50 x 5.20 x 5.30 Shipping Ximage (http://www.comstruction) Shipping Ximage (http://www.comstruction) Uhit Weight (bs.) 0.10 Uhit Weight (bs.) O.00 x 0.000 x 0.000 Uhit Weight (bs.) 0.05 O.02 Statestruction ENVIRONTAL 0.05 O.22 Statestruction Statestruction (http://www.comstruction) Storage Temperature Range 32* to 158*F (0* to 70*C) Statestruction (http://www.comstruction) Statestruction (http://www.comstruction) Bitable MunitickTons 2.6 strUHr States Uhit (http://www.comstruction) State Struction (http://www.comstructi		
Power Power Consumption (Watts) 0.75 PhysicAL Color Black Material of Construction ABS, PVC Color Black Material of Construction ABS, PVC Color 0.50 x 5.20 x 5.30 Shipping Dimensions (hvd /in.) 0.50 x 5.20 x 5.30 Shipping Dimensions (hvd /in.) 0.50 x 5.20 x 5.30 Shipping Ximage (http://www.comstruction) ABS, PVC Uhit Dimensions (hvd /in.) 0.50 x 5.20 x 5.30 Shipping Ximage (http://www.comstruction) Shipping Ximage (http://www.comstruction) Uhit Dimensions (hvd /in.) 0.50 x 5.20 x 5.30 Shipping Ximage (http://www.comstruction) Shipping Ximage (http://www.comstruction) Uhit Weight (bs.) 0.10 Uhit Weight (bs.) O.00 x 0.000 x 0.000 Uhit Weight (bs.) 0.05 O.02 Statestruction ENVIRONTAL 0.05 O.22 Statestruction Statestruction (http://www.comstruction) Storage Temperature Range 32* to 158*F (0* to 70*C) Statestruction (http://www.comstruction) Statestruction (http://www.comstruction) Bitable MunitickTons 2.6 strUHr States Uhit (http://www.comstruction) State Struction (http://www.comstructi	Bus Powered	Yes
Pewer Consumption (Watts) 0.75 PHYSICAL Color Black Color Black Color Material of Construction ABS. PVC Cable Jacket Rating VW-1 Shipping Dimensions (hwd / in.) 0.50 x 5.20 x 5.30 Shipping Weight (Ibs.) 0.10 Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000 Unit Weight (Ibs.) 0.05 Dorealing Temperature Range 32° to 158°F (0° to 70°C) Storage Temperature Range 32° to 158°F (0° to 70°C) Storage Temperature Range 32° to 158°F (0° to 70°C) Storage Temperature Range 32° to 158°C (1° to 80°C) Relative Humidty 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr Communications 22.8 BTU/Hr IEEE Standards Supported 802.3 so2.3ay: 802.3y: 802.3y: 802.3y: 802.3y Side A - Connector 1 IUSB A (MAL	Product Length (in.)	7.5
PHYSICAL Color Black Color ABS, PVC Color Cable Jacket Raing VV-1 Shipping Dimensions (hvd / in.) D.50 x 5.20 x 5.30 Shipping Dimensions (hvd / in.) D.50 x 5.20 x 5.30 Shipping Dimensions (hvd / in.) D.50 x 5.20 x 5.30 Unit Dimensions (hvd / in.) D.000 x 0.000 x 0.000 O.000 O.000 Unit Weight (bs.) D.05 O.05 O.05 Unit Weight (lbs.) D.05 O.05 Unit Weight (lbs.) D.05 O.02 ENVIRONMENTAL Operating Temperature Range 32* to 158°F (0° to 70°C) Storage Temperature Range 14* to 176°F (-10° to 80°C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr COMMUNICATIONS Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3 ab: 802.3az; 802.3az; 802.3ax S02 CONNECTIONS Side A - Connector 1 RJ45 (FEMALE) Connector 1 Side B - Connector 1 RJ45 (FEMALE) Connector 1 RJ45 (FEMALE) Connector Plating Nickel FETURE	POWER	
Color Black Material of Construction ABS, PVC Cable Jacket Rating VW-1 Shipping Dimensions (twd / in.) 0.50 x 5.20 x 5.30 Shipping Weight (bs.) 0.10 Unit Dimensions (twd / in.) 0.000 x 0.000 Unit Dimensions (twd / in.) 0.000 x 0.000 Unit Weight (bs.) 0.06 Unit Weight (bs.) 0.06 Unit Weight (bs.) 0.06 Unit Weight (bs.) 0.06 Unit Weight (bs.) 0.02 Perviconmental 0.02 Enviconmental 0.02 Storage Temperature Range 32" to 158"F (0" to 70"C) Storage Temperature Range 14" to 176"F (-10" to 00"C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr Communications 2.6 BTU/Hr Communications 2.3, 802.3ab; 802.3bb;	Power Consumption (Watts)	0.75
ABS. PVC Cable Jacket Rating VW-1 Shipping Dimensions (twd / in.) 0.50 x 5.20 x 5.30 Shipping Dimensions (twd / in.) 0.10 Unit Dimensions (twd / in.) 0.000 x 0.000 Unit Dimensions (twd / in.) 0.000 x 0.000 Unit Weight (bs.) 0.05 Storage Temperature Range 32* to 158*F (0* to 70*C) Storage Temperature Range 14* to 176*F (-10* to 80*C) Relative Humidity 10% to 80 % RH, Non-Condensing BTUs 2.6 BTU/Hr Commetor Easter 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3; 802.3; 802.3; 802.3; Side A - Conne	PHYSICAL	
Cable Jacket Rating VW-1 Shipping Dimensions (twd / in.) 0.50 x 5.20 x 5.30 Shipping Weight (bs.) 0.10 Unit Dimensions (twd / in.) 0.000 x 0.000 x 0.000 Unit Dimensions (twd / in.) 0.000 x 0.000 x 0.000 Unit Dimensions (twd / in.) 0.000 x 0.000 x 0.000 Unit Weight (bs.) 0.05 Unit Weight (bs.) 0.05 Unit Weight (bs.) 0.02 ENVIRONMENTAL 0.02 Operating Temperature Range 14" to 176"F (-10" to 80"C) Storage Temperature Range 14" to 176"F (-10" to 80"C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr COMUNICATIONS 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.38: 802.38: 802.38: 802.38: Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) Side B - Connector 1 RJ45 (FEMALE) Connector 1 RJ45 (FEMALE) Connector Plating Wick	Color	Black
Shipping Dimensions (twd / in.) 0.50 x 5.20 x 5.30 Shipping Weight (bs.) 0.10 Unit Dimensions (twd / in.) 0.000 x 0.000 x 0.000 Unit Dimensions (twd / in.) 0.000 x 0.000 x 0.000 Unit Dimensions (twd / in.) 0.000 x 0.000 x 0.000 Unit Veight (bs.) 0.05 Unit Weight (bs.) 0.05 Unit Weight (bs.) 0.02 ENVIRONMENTAL 0.02 Storage Temperature Range 32* to 158*F (0° to 70°C) Storage Temperature Range 14* to 176*F (-10° to 80°C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr COMMUNICATIONS 802.3; 802.3az; 802.3az; 802.3az Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3az; 802.3az; 802.3az CONNECTIONS Side A - Connector 1 Side B - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Suppo	Material of Construction	ABS, PVC
Shipping Weight (bs.) 0.10 Unit Dimensions (hwd / in.) 0.000 x 0.000 Unit Packaging Type Box Unit Weight (bs.) 0.05 Unit Weight (kg) 0.02 ENVIRONMENTAL Operating Temperature Range 32* to 158*F (0* to 70*C) Storage Temperature Range 14* to 176*F (-10° to 80°C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr COMMUNICATIONS Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3az; 802.3az; 802.3ay CONNECTIONS Side A - Connector 1 Side B - Connector 1 USB A (MALE) Side B - Connector 1 RJ46 (FEMALE) Connector 1 Nickel FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	Cable Jacket Rating	VW-1
Unit Dimensions (hwd / in.) 0.000 x 0.000 Unit Packaging Type Box Unit Weight (bs.) 0.05 Unit Weight (kg) 0.02 ENVRONMENTAL Doperating Temperature Range 22° to 158°F (0° to 70°C) Storage Temperature Range Storage Temperature Range 14° to 176°F (-10° to 80°C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr COMMUNICATIONS 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3s (802.3az; 802.3az; 802.3x; Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FutURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes	Shipping Dimensions (hwd / in.)	0.50 x 5.20 x 5.30
Unit Packaging Type Box Unit Weight (bs.) 0.05 Unit Weight (kg) 0.02 ENVIRONMENTAL Operating Temperature Range 32° to 158°F (0° to 70°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr COMMUNICATIONS 100 Mbps (Fast Ethernet) Relative Auger 802.3; 802.3a; 802.3a; 802.3a; 802.3x CONNECTIONS 802.3; 802.3a; 802.3a; 802.3a; 802.3x Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel PEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) Lus A pupprit Yes	Shipping Weight (lbs.)	0.10
Unit Weight (bs.) 0.05 Unit Weight (kg) 0.02 ENVIRONMENTAL Operating Temperature Range 32° to 158°F (0° to 70°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr COMMUNICATIONS 100 Mbps (Fast Ethernet) Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3az; 802.3u; 802.3x CONNECTIONS Side A - Connector 1 Side A - Connector 1 USB A (MALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000
Unit Weight (kg) 0.02 ENVIRONMENTAL Seven 158°F (0° to 70°C) Storage Temperature Range 32° to 158°F (0° to 70°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr COMMUNICATIONS 802.3; 802.3az; 802.3u; 802.3x Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3az; 802.3u; 802.3x CONNECTIONS Side A - Connector 1 Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	Unit Packaging Type	Box
ENVIRONMENTAL Operating Temperature Range 32° to 158°F (0° to 70°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr COMMUNICATIONS 2.6 BTU/Hr Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3az; 802.3u; 802.3x CONNECTIONS 802.3; 802.3az; 802.3u; 802.3x Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	Unit Weight (lbs.)	0.05
Operating Temperature Range 32° to 158°F (0° to 70°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr communications Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3az; 802.3u; 802.3x connector 1 Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel PECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes	Unit Weight (kg)	0.02
Storage Temperature Range 14° to 176°F (-10° to 80°C) Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr communications Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3ab; 802.3az; 802.3u; 802.3x connectrons Side A - Connector 1 Side B - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	ENVIRONMENTAL	
Relative Humidity 10% to 90 % RH, Non-Condensing BTUs 2.6 BTU/Hr commUNICATIONS Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3a2; 802.3u; 802.3x connector 1 Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	Operating Temperature Range	32° to 158°F (0° to 70°C)
BTUs 2.6 BTU/Hr COMMUNICATIONS Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3ab; 802.3az; 802.3u; 802.3x CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 Side B - Connector 1 Nickel Connector 1 BTUSB X SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	Storage Temperature Range	14° to 176°F (-10° to 80°C)
COMMUNICATIONS Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3ab; 802.3az; 802.3u; 802.3x CONNECTIONS Side A - Connector 1 Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	Relative Humidity	10% to 90 % RH, Non-Condensing
Network Compatibility 100 Mbps (Fast Ethernet) IEEE Standards Supported 802.3; 802.3ab; 802.3az; 802.3x CONNECTIONS Side A - Connector 1 Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	BTUs	2.6 BTU/Hr
IEEE Standards Supported 802.3; 802.3ab; 802.3az; 802.3u; 802.3x connectrions Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	COMMUNICATIONS	
CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	Network Compatibility	100 Mbps (Fast Ethernet)
Side A - Connector 1 USB A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	IEEE Standards Supported	802.3; 802.3ab; 802.3az; 802.3u; 802.3x
Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	CONNECTIONS	
Connector Plating Nickel FEATURES & SPECIFICATIONS USB Specification USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	Side A - Connector 1	USB A (MALE)
FEATURES & SPECIFICATIONS USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	Side B - Connector 1	RJ45 (FEMALE)
USB Specification USB 2.0 (up to 480 Mbps) Auto MDIX Support Yes Full Duplex Support Yes	Connector Plating	Nickel
Auto MDIX Support Yes Full Duplex Support Yes	FEATURES & SPECIFICATIONS	
Full Duplex Support Yes	USB Specification	USB 2.0 (up to 480 Mbps)
	Auto MDIX Support	Yes
Suspend Mode Support Yes	Full Duplex Support	Yes
	Suspend Mode Support	Yes



1000 Eaton Boulevard Cleveland, OH 44122 United States

Remote Wakeup Support	Yes	
Driver Required	Yes	
Recommended Category Cable	Cat5/Cat5e/Cat6 Cables	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.