



Electronics module for IO-Link, black, 8 inputs/outputs, 4DI/4DQ, Push-in, for floor mounting

<b>product brand name</b>	SIRIUS ACT
<b>product designation</b>	Electronic module for IO-Link
<b>product type designation</b>	3SU1
<b>General technical data</b>	
insulation voltage rated value	30 V
<b>degree of pollution</b>	3
<b>type of voltage</b>	
• of the operating voltage	DC
• of the input voltage	DC
<b>surge voltage resistance rated value</b>	0.8 kV
consumed current maximum	41 mA
<b>protection class IP</b>	IP20
shock resistance for railway applications according to EN 61373	Category 1, Class B
vibration resistance for railway applications according to EN 61373	Category 1, Class B
<b>reference code according to IEC 81346-2</b>	P
<b>Substance Prohibitance (Date)</b>	10/01/2014
operating voltage rated value	18 ... 30 V
operating voltage 1 at DC rated value	24 V
<b>Communication/ Protocol</b>	
<b>protocol is supported</b>	
• AS-Interface protocol	No
• IO-Link protocol	Yes
<b>IO-Link transfer rate</b>	COM2 (38,4 kBaud)
<b>point-to-point cycle time between master and IO-Link device minimum</b>	10 ms
<b>type of voltage supply via input/output link master</b>	Yes
<b>data volume</b>	
• of the address range of the inputs with cyclical transfer total	3 byte
• of the address range of the outputs with cyclical transfer total	1 byte
<b>Inputs/ Outputs</b>	
<b>number of digital inputs</b>	4
<b>number of digital outputs</b>	4
<b>Connections/ Terminals</b>	
<b>type of electrical connection</b>	spring-loaded terminal (push-in)
<b>type of connectable conductor cross-sections</b>	
• solid with core end processing	1x (0.14 ... 0.5 mm <sup>2</sup> )

- solid without core end processing
- finely stranded without core end processing
- at AWG cables

1x (0.14 ... 0.5 mm<sup>2</sup>)  
 1x (0.2 ... 0.5 mm<sup>2</sup>)  
 1x (26 ... 20)

#### Product Function

suitability for use safety-related circuits No

#### Ambient conditions

##### ambient temperature

- during operation
- during storage

-25 ... +70 °C  
 -40 ... +80 °C

environmental category during operation according to IEC 60721

3M6, 3S2, 3B2, 3C3 (without salt spray), 3K6 (with relative humidity of 10 ... 95%, no condensation in operation permitted)

#### Installation/ mounting/ dimensions

fastening method of modules and accessories Floor mounting

height 57.5 mm

width 23.8 mm

depth 53.5 mm

#### Measuring circuit

product function 4DI / 4DO

#### Certificates/ approvals

General Product Approval

Declaration of Conformity

Test Certificates

[Confirmation](#)



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

#### other

[Environmental Confirmations](#)

[Confirmation](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1400-2HM10-6AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1400-2HM10-6AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1400-2HM10-6AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1400-2HM10-6AA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1400-2HM10-6AA0&lang=en)

last modified:

1/27/2022