



NOTES: Finish (Plating Thickness in Micro-inches)  
 1. Brass  
 2. Thin Gold over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick  
 3. Beryllium Copper  
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick  
 5. Teflon

RoHS Compliant

Remark:  
 1. Max. Panel Thickness = .256 (6.5)

Dimensions are in Inches			
Unless Otherwise Specified Tolerances			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	

Part No.	
Approved	Date 7-10-2015
Checked	Date 7-10-2015
Drawn	Date 7-10-2015

<b>NTE Electronics</b>	
Title	SMA Bulkhead Jack to Jack Adapter
Drawing No.	06-S007
File No.	

5	Hex-Nut	Note 1	Note 2	1	
4	Lock Washer	Note 1	Note 2	1	
3	Contact Pin	Note 3	Note 4	1	
2	Insulator	Note 5	Natural	2	
1	Body	Note 1	Note 2	1	
No	Description	Material	Finish	Q'ty	Drawing No.

Scale	5/1	Issue	A
-------	-----	-------	---

A

A