ATGBICS JNP-QSFP-DAC-2M Juniper Compatible Direct Attach Copper Twinax Cable 40G QSFP+ (2m, Passive)

Brand : ATGBICS

Product code: JNP-QSFP-DAC-2M-C

Product name : JNP-QSFP-DAC-2M Juniper Compatible Direct Attach Copper Twinax Cable 40G QSFP+ (2m, Passive)

JNP-QSFP-DAC-2M Juniper Compatible Direct Attach Copper Twinax Cable 40G QSFP+ (2m, Passive)

ATGBICS JNP-QSFP-DAC-2M Juniper Compatible Direct Attach Copper Twinax Cable 40G QSFP+ (2m, Passive):

ATGBICS JNP-QSFP-DAC-2M compatible 40GBase-CU QSFP+ to QSFP+ direct attach cable operates over passive copper with a cable length of 2m. It is suitable for short reach connection between two QSFP+ ports in 40G interconnecting networking applications. Our product meets the specification of Juniper JNP-QSFP-DAC-2M= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; 40G InfiniBand 8x DDR, 4x QDR, IEEE 802.3ba 40Gigabit Ethernet, Fibre Channel, MSA QSFP+ SFF-8436 compliant.


ATGBICS JNP-QSFP-DAC-2M Juniper Compatible Direct Attach Copper Twinax Cable 40G QSFP+ (2m, Passive). Cable length: 2 m, Connector 1: QSFP+, Connector 2: QSFP+, Data transfer rate: 40000 Mbit/s







| Features | | Features | |
|---|---|---|--|
| Product colour * Cable length * Connector 1 * Connector 2 * | Black 2 m QSFP+ QSFP+ Male Polyvinyl chloride (PVC) Copper 40 Gigabit Ethernet IEEE 802.3ba 30 40000 Mbit/s ✓ CE, FCC, RoHS | Country of origin Operational conditions Operating temperature (T-T) Storage temperature (T-T) | United Kingdom 0 - 70 °C -40 - 80 °C |
| Connector 1 gender * Connector 2 gender * Jacket material Conductor material | | Operating relative humidity (H-H) Storage relative humidity (H-H) Packaging data | 10 - 90% 10 - 85% |
| Ethernet interface type Networking standards AWG wire size | | Quantity per pack Technical details | 1 pc(s) |
| Data transfer rate Plug and Play Certification | | Sustainability compliance Sustainability certificates Doesn't contain | ✔ RoHS Lead |



5056468723444

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.