Data sheet 27142.5 PQI 4/2 BU



Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 10.1 mm, Colour: Blue

RAL: Ähnlich 5005

Business data

Article number	<u>27142.5</u>
Article name	PQI 4/2 BU
GTIN (EAN)	4044211226862
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	1.7 g
Weight per piece (including packaging)	1.75 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	27142.9
Product description	Insulated cross-connector
· · · · · · · · · · · · · · · · · · ·	

Data sheet





Tankwinal data		
Technical data Dimensions		
Length	4 mm	
Width	10.1 mm	
Height	19.4 mm	
Pitch size	6.1 mm	
Ratings		
Max. voltage	800 V	
Rated current	32 A	
Current load, max.	32 A	
Rated cross-section	4 mm²	
Contamination degree	3	
Connection data		
No. of poles	2	
Materials		
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-0	
Working temperature, min.	-40 °C	
Working temperature, max.	120 °C	
Further technical data		
Mounting type	Plug in	
Insulation available	✓	
Touch protection is available	✓	
Number of bridged terminals	2	
Environmental Product Compliance		
REACH Conform	yes	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

Data sheet 27142.5 PQI 4/2 BU



Media

Data sheet

27142.5 PQI 4/2 BU



Accessories

##INVERSE##CONTA-CONNECT



Three-level initiator terminal |Multi-wire terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27046.6	PVMAK 2,5 GR	4044211227289	50 ST



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27013.2	PSL 4/2A GNYE	4044211215804	50 ST



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27015.2	PSL 4/3A GNYE	4044211215842	50 ST



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
27017.2	PSL 4/4A GNYE	4044211215880	50 ST



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27016.6	PRK 4/4A GR	4044211215873	50



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27012.6	PRK 4/2A GR	4044211215774	50

Data sheet





##INVERSE##CONTA-CONNECT



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5,Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
27014.6	PRK 4/3A GR	4044211215835	50

##INVERSE##CONTA-CONNECT