

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A3		ECR-15-007632	25MAY2015	DW	CW
B		ECR-15-014907	14OCT2015	DL	CW
B1		ECR-16-015492	09NOV2016	QY	CW
C		ECR-21-108559	06AUG2021	BS	CW

M4 SCREW,  
RECOMMENDED  
TIGHTENING TORQUE 1.2Nm  
M4螺丝, 推荐锁紧力矩 1.2Nm

4X M3 SCREW, RECOMMENDED  
TIGHTENING TORQUE 0.5Nm  
4X M3螺丝, 推荐锁紧力矩 0.5Nm

NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 500 V  
RATED CURRENT: 16 A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 6 KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
WIRE RANGE: 0.14-4 mm<sup>2</sup> (26-12 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING: T20300X20XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 500V  
额定电流: 16A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 6 KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
接线范围: 0.14-4 mm<sup>2</sup> (26-12 AWG)  
接线类型: 冷压接
- 端子需要单独订购.  
(订货号参考图面: T20300X20XX000)

PANEL CUT FOR INSERTS FOR USE  
WITHOUT HOODS/ HOUSINGS  
不使用防护外壳时芯件的安装开孔图

TYPE-1, T2050322201-000, WITH TE LOGO  
类型-1, T2050322201-000, 带TE LOGO

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN		TE Connectivity	
mm				11JUN2014		HEE-032-F	
		0 PLC	±-	CHK	11JUN2014		
		1 PLC	±-	APVD	11JUN2014		
		2 PLC	±-	PRODUCT SPEC	108-106137		
		3 PLC	±-	APPLICATION SPEC	114-106137		
MATERIAL		4 PLC	±-	WEIGHT	-	SIZE	A3
-		ANGLES	±-	FINISH	-	CAGE CODE	00779
-						DRAWING NO	T2050322201000
						RESTRICTED TO	-
						SCALE	1:1
						SHEET	1 OF 2
						REV	C

1470-19 (3/13)

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

REVISIONS

© COPYRIGHT 20 BY - ALL RIGHTS RESERVED.


P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-

NOTE:  
ALL SPEC REFER TO TYPE 1

注释:  
所有产品规范参照 TYPE 1

TYPE-2, T2050322201-001, WITH STAINLESS STEEL SCREW, WITHOUT LOGO  
类型-2, T2050322201-001, 带不锈钢螺丝, 无LOGO

T2050322201-001	HEE-032-F	HEE-032 FEMALE INSERT, WITH STAINLESS STEEL SCREW, WITHOUT LOGO HEE-032 母插, 带不锈钢螺丝, 无LOGO	TYPE-2 类型-2
T2050322201-000	HEE-032-F	HEE-032 FEMALE INSERT HEE-032 母插	TYPE-1 类型-1
PART NUMBER 料号	PART DESCRIPTION 描述		TYPE 类型

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 11 JUN 2014 David Wang	 TE Connectivity					
DIMENSIONS: mm		CHK 11 JUN 2014 Chris Wang			NAME HEE-032-F			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 11 JUN 2014 Xiang Xu			PRODUCT SPEC 108-106137			
0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±-		APPLICATION SPEC 114-106137	SIZE A3	CAGE CODE 00779	DRAWING NO T2050322201000	RESTRICTED TO -		
MATERIAL -		FINISH -	WEIGHT -	Customer Drawing		SCALE 1:1	SHEET 2 OF 2	REV C

1470-19 (3/13)