## Data sheet 28700.4 KDS-SR-FB1/A BK





Cable entry with injected seal, Mounting type: Screws, Length: 73 mm, Width: 39 mm, IP 66, Colour: Black

**RAL:** 9005

#### **Business data**

28700.4
KDS-SR-FB1/A BK
4044211225476
10
PC
28.2 g
31.7 g
G
39259020
DE
Cable Entry
Black

# Data sheet 28700.4 KDS-SR-FB1/A BK





Technical data		
Dimensions		
Length	73 mm	
Lenght of wall cutout	46 mm	
Width	39 mm	
Width of wall cutout	24 mm	
Height	19 mm	
Installation height	18.9 mm	
Diameter of the screw holes	5.5 mm	
Materials		
Material	Polyamide 6.6	
Glass-fibre reinforced	✓	
Flammability class UL 94	V-0	
Working temperature, min.	-40 °C	
Working temperature, max.	120 °C	
Sealing material	TPE	
Halogen-free	✓	
Silicone-free	✓	
Further technical data		
Mounting type	Screws	
Degree of protection	IP66	
Number of screw holes	2	
Fixing screws	M 5 (ISO 4762 / DIN 912)	
Torque of the fixing screws	3 Nm	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-01-17	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

## Data sheet 28700.4 KDS-SR-FB1/A BK



### Media





### Data sheet





#### **Accessories**

_						
Е	lat	ca	h	А	802	ıc



Seal, Mounting type: Plug in, Length 42.7 mm, Width: 20.3 mm, IP 66, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28717.6</u>	KDS-DE-FB1/E GR	4044211221102	5 ST



Seal, Mounting type: Plug in, Length 42.7 mm, Width: 20.3 mm, IP 66, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
28718.6	KDS-DE-FB1/F GR	4044211221119	5 ST



Seal dummy, Mounting type: Plug in, Length 42.7 mm, Width: 20.3 mm, IP 66, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
28713.6	KDS-DE-FB1/A GR	4044211221065	5 ST



Seal, Mounting type: Plug in, Length 42.7 mm, Width: 20.3 mm, IP 66, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
28714.6	KDS-DE-FB1/B GR	4044211221072	5 ST



Seal, Mounting type: Plug in, Length 42.7 mm, Width: 20.3 mm, IP 66, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28715.6</u>	KDS-DE-FB1/C GR	4044211221089	5 ST



Seal, Mounting type: Plug in, Length 42.7 mm, Width: 20.3 mm, IP 66, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
28716.6	KDS-DE-FB1/D GR	4044211221096	5 ST

#### **Actuating tool**

### 28700.4 KDS-SR-FB1/A BK





Using the KDS BW1 actuating tool, the seals can be conveniently mounted in and dismantled from the frame. The ergonomic grip and the special shape enable simple and precise installations, especially for cabling applications in confined spaces., Material: Polyamide

Article number	Article name	GTIN (EAN)	Packaging unit
28622.0	KDS BW 1	4044211216597	1 ST

#### **Sheet-metal puncher**



Sheet metal puncher for rectangular openings, Dimensions opening: 46 x 24 mm, Maximum wall thickness: 2.0 mm for stainless steel sheet, Material: steel

Article number	Article name	GTIN (EAN)	Packaging unit
28734.0	BL KDS-FB1	4044211221805	1 ST



Sheet metal puncher for rectangular openings, Dimensions opening: 46 x 24 mm, Maximum wall thickness: 2.0 mm for stainless steel sheet, Material: steel

Article number	Article name	GTIN (EAN)	Packaging unit
28729.0	BL-VA KDS-FB1	4044211221768	1 ST

#### **EMC** brackets



Shield-connection rail enabling mounting of shield connection clips directly on cable entry system KDS, Mounting type: Screw, Length: 35,3 mm, Width: 68 mm, Height: 16 mm, Profile: 10x3 mm

Article number Article name GTIN (EAN)

28623.0 KDS-EMV-SAB 1-4

4044211219628

1 ST

#### ##INVERSE##CONTA-CABLE



Seal, Mounting type: Plug in, Length 42.7 mm, Width: 20.3 mm, IP 66, Colour: Grey

Article number	Article name	GTIN (EAN)	Packaging unit
28716.6	KDS-DE-FB1/D GR	4044211221096	5 ST