



TECHNICAL

AGENCY APPROVAL: cULus
 RATED SUPPLY VOLTAGE: 120VAC
 RATED CURRENT: UP TO 15 AMPS
 RESET TYPE: MANUAL
 OPERATING FREQUENCY: 60 Hz
 TYPE: CLASS A
 GROUND TRIP CURRENT: 4-6 mA
 OVERLOAD CURRENT: 90 AMP
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE
 ENDURANCE OPERATIONS: 3000 OPERATIONS

MATERIAL NUMBER	ENGINEERING NUMBER	LENGTH "A"	LENGTH "L"
1301530019	15050-1	1 FT.	2 FT. ± 1 IN.
1301530036	15050-6	5 FT.	6 FT. ± 2 IN.
1301530022	15050-25	24 FT.	25 FT. ± 2 IN.
NA	15050-50	49 FT.	50 FT. ± 2 IN.

FUNCTIONAL SYMBOLS $\nabla_A = 0$ $\nabla_C = 0$ $\nabla_P = 0$	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: UPDATED PLUG AND CONNECTOR.			
	DIMENSION UNITS	SCALE	EC NO: 730358			
	INCH	NTS	DRWN: PPURSUTANDEL 2022/11/29			
	GENERAL TOLERANCES (UNLESS SPECIFIED)		CHK'D: DNGUYEN62 2023/02/17			
DIVISIONAL SYMBOLS 4 PLACES ± 3 PLACES ± 2 PLACES ± 1 PLACE ± 0 PLACES ±	ANGULAR TOL ± °	APPR: HKNEELAND 2023/02/21		PRODUCT CUSTOMER DRAWING		
	INITIAL REVISION:		DOCUMENT NUMBER		DOC TYPE	DOC PART
	DRWN: PPURSUTANDEL 2022/01/04		1301530019		PSD	000
	APPR: HKNEELAND 2022/01/20		SERIES		REVISION	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SHEET NUMBER	MATERIAL NUMBER	
			C-SIZE	130153	SEE TABLE	
					CUSTOMER	
					GENERAL MARKET	
					SHEET NUMBER	
					1 OF 1	