

Product data sheet

Specifications



Float kit, 9049, switch accessory stainless steel 304 rod

9049A6CS

Main

Range of product	9049
Product or component type	Float kit

Complementary

Product compatibility	9038A 9036G 9036D
-----------------------	-------------------------

Kit composition	1 float 2 rod 4 stop
-----------------	----------------------------

Rod length	1.52 m stainless steel 304
------------	----------------------------

Type of float	Center hole float stainless steel 304
---------------	---------------------------------------

Condition of use	Maximum recommended tubing length: 30 ft
------------------	--

Net buoyancy	70 ozf in water
--------------	-----------------

Product weight	170.10 g total weight of stops 479.12 g weight of 5 ft rod 96.39 g weight of extra rod (per ft) 2.75 kg total weight
----------------	---

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	19.677 cm
------------------	-----------

Package 1 Width	7.747 cm
-----------------	----------

Package 1 Length	49.98 cm
------------------	----------

Package 1 Weight	2.749 kg
------------------	----------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
-------------------	---

Mercury free	Yes
--------------	-----

RoHS exemption information	Yes
----------------------------	---------------------

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty 18 months

Recommended replacement(s)