THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PACKAGE CONTENTS						
RETROFIT KIT PART NUMBER	COPPER WIRE ONLY RUN AWG "CODE WIRE" Class B or C Stranded		ITEM DESCRIPTION	QTY ITEM IN KIT	ITEM PART NUMBER	PACKAGE WEIGHT LBS [KG]
	MIN.	MAX.				
VS-AVT-RKP1	14 SOL 14 STR	6 SOL 6 STR	VERISAFE INSULATION-PIERCING CONNECTOR KIT	1	VS-CKP14-6	5.74 [2.60]
			VERISAFE AVT	1	VS-AVT-C08-L10	
			CABLE TIE	12	PLT1.5I-C	
			CABLE TIE MOUNT	6	ABM112-AT-C	
			MARKER CARD	1	-	
VS-AVT-RKP2	4 SOL 4 STR	3/0 STR	VERISAFE INSULATION-PIERCING CONNECTOR KIT	1	VS-CKP4-000	6.08 [2.76]
			VERISAFE AVT	1	VS-AVT-C08-L10	
			CABLE TIE	12	PLT1.5I-C	
			CABLE TIE MOUNT	6	ABM112-AT-C	
			MARKER CARD	1	-	

NOTES, UNLESS OTHERWISE SPECIFIED:
1. DIMENSIONS IN BRACKETS ARE METRIC.
2. REFER TO WWW.PANDUIT.COM FOR COMPLETE INSTALLATION REQUIREMENTS AND USAGE LIMITATIONS FOR PANDUIT INSULATION-PIERCING CONNECTORS.
3. REFER TO WWW.PANDUIT.COM FOR COMPLETE INSTALLATION REQUIREMENTS AND USAGE LIMITATIONS FOR PANDUIT FERRULES.

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
00	9/12/2018	BKA	JBN	BKA	RELEASED	040528

TITLE

VS-AVT-RKP Series VeriSafe Retrofit Kits (with Insulation-Piercing Connectors)

CUSTOMER DRAWING

ITEM REVISION NAME: 00080EAX/00

DATASET FILE NAME: 00080EAX_DC/00

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]

.X ± .1 [2.54] .XXX ± .005 [.127]
.XX ± .01 [.25] ANGLES ± 5 °

THIRD ANGLE PROJECTION

MATERIAL: N/A

DRAWING NUMBER: 00080EAX-DC

DRAWN BY	DATE	CHK	SCALE		SIZE
BKA	9/12/2018	BKA	NONE	SHT 1 OF 1	A

D10100DA/20