

# 4-Outlet Power Strip, 6 ft. (1.83 m) Cord, 5-15P, 12 in.

MODEL NUMBER: PS120406









#### **Highlights**

- Ideal for applications needing multiple convenience outlets for powering a variety of electronic equipment
- 12-in. mountable housing with 4 standard NEMA 5-15R outlets and a 6-ft. power cord
- Lighted, covered On/Off switch and 15-amp circuit breaker
- Sturdy construction and heavyduty, all-metal housing

### **Package Includes**

- PS120406
- Mounting hardware
- · Instruction manual

The PS120406 power strip provides horizontal or vertical power distribution for rackmount, raceway and workbench applications in a convenient 12-in. mountable housing.

#### **Features**

**Multi-Outlet Power Distribution** 

**Vertical or Horizontal Moun** 

**Premium Safety Features** 

**Heavy-Duty Housing** 

## **Specifications**

OVERVIEW		
UPC Code	037332186119	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	6	



Right-Angle Plug         No           Input Cord Length (m)         1.83           Integrated Cord Clip         No           OUTPUT           Frequency Compatibility         60 Hz           Cutzuit Breaker (amps)         15           Transformer Accommodation         (2) Yes           Right-Angle Outlets         No           Outlet Spacing         1.77 in.           USER INTERFACE, ALERTS & CONTROLS           Switches         Lighted 2 position switch controls power to all outlets           Locking Switch Cover         Transparent on/off switch cover prevents accidental turn-off           PHYSICAL           Color         Silver           Material of Construction         Aluminum           Power Cost Color         Black           Form Factors Supported         Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications (housed Mounting Accessories)         Included Mounting Accessories           Mounting Holes or Siots         No           Outlets Measurement (Center to content)         1.77 in.           Receptacle Color         Black           Shipping Dimensions (twd / in)         3.03 x 3.58 x 15.55           Shipping Weight (tbs.)         1.78 </th <th></th> <th>1</th>		1	
No	Right-Angle Plug	No	
OUTPUT Frequency Compatibility 60 Hz Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (2) Yes Right-Angle Outlets No Outlet Spacing 1.77 in.  USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off  PHYSICAL Color Silver Material of Construction Aluminum Power Cord Color Black Form Factors Supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Housing Color Silver Included Mounting Accessories Includes mounting clips Mounting Holes or Sicis No Outlets Measurement (Center to Center) 1.77 in. Receptacle Color Black Shipping Dimensions (hwd / in.) 3.03 x 3.58 x 15.55 Shipping Dimensions (hwd / cm) 7.70 x 9.09 x 39.50 Shipping Weight (bs.) 1.78 Shipping Weight (kg) 0.88 Unit Weight (kg) 0.58	Input Cord Length (m)	1.83	
Frequency Compatibility         60 Hz           Output Receptacles         (4) 5-15R           Circuit Breaker (amps)         15           Transformer Accommodation         (2) Yes           Right-Angle Outlets         No           Output Spacing         1.77 in.           USER INTERFACE, ALERTS & CONTOLS           Switches         Lighted 2 position switch controls power to all outlets           Locking Switch Cover         Transparent on/off switch cover prevents accidental turn-off           PHYSICAL           Color         Sliver           Material of Construction         Aluminum           Power Cord Color         Black           From Factors Supported         Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications           Housing Color         Silver           Included Mounting Accessories         Includes mounting clips           Mounting Holes or Slots         No           Outlets Measurement (Center to Content)         3.03 x 3.58 x 15.55           Shipping Dimensions (hwd / in)         3.03 x 3.58 x 15.55           Shipping Dimensions (hwd / cm)         7.70 x 9.09 x 39.50           Shipping Weight (bs)         1.78           Shipping Weight (bs)         0.81	Integrated Cord Clip	No	
Output Receptacles         (4) 5-15R           Circuit Breaker (amps)         15           Transformer Accommodation         (2) Yes           Right-Angle Outlets         No           Outlet Spacing         1,77in.           USER INTERFACE, ALERTS & CONTROLS           Switches         Lighted 2 position switch controls power to all outlets           Locking Switch Cover         Transparent on/off switch cover prevents accidental turn-off           PHYSICAL           Color         Silver           Material of Construction         Aluminum           Power Cord Color         Black           Form Factors Supported         Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications           Housing Color         Silver           Included Mounting Accessories         Includes mounting clips           Mounting Holes or Silots         No           Cullatis Measurement (Center to Center)         1,77 in.           Receptacle Color         Black           Shipping Dimensions (twd / in.)         3,03 x 3.58 x 15.55           Shipping Weight (kg)         0,81           Unit Dimensions (twd / in.)         1,250 x 1.620 x 12.000           Unit Dimensions (twd / in.)         3,18 x 4.12 x 30.48	OUTPUT		
Circuit Breaker (amps)         15           Transformer Accommodation         (2) Yes           Right-Angle Outlets         No           USER INTERFACE, ALERTS & CONTROLS           Switches         Lighted 2 position switch controls power to all outlets           Locking Switch Cover         Transparent on/off switch cover prevents accidental turn-off           PHYSICAL           Color         Silver           Material of Construction         Aluminum           Power Cord Color         Black           Form Factors Supported         Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications           Housing Color         Silver           Included Mounting Accessories         Includes mounting clips           Mounting Holes or Slots         No           Outlets Measurement (Center to Center to Shipping Dimensions (hwd / in)         3.03 x 3.58 x 16.56           Shipping Dimensions (hwd / cm)         7.70 x 9.09 x 39.50           Shipping Weight (lbs)         1.78           Shipping Weight (kg)         0.81           Unit Dimensions (hwd / in)         1.250 x 1.620 x 12.000           Unit Weight (kg)         0.58	Frequency Compatibility	60 Hz	
Transformer Accommodation         (2) Yes           Right-Angle Outlets         No           USER INTERFACE, ALERTS & CONTOLS           Switches         Lighted 2 position switch controls power to all outlets           Locking Switch Cover         Transparent on/off switch cover prevents accidental turn-off           PHYSICAL           Color         Sliver           Material of Construction         Aluminum           Power Cord Color         Black           Form Factors Supported         Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications           Housing Color         Silver           Included Mounting Accessories         Includes mounting clips           Mounting Holes or Slots         No           Outlets Measurement (Center to Center to Center)         1.77 in.           Shipping Dimensions (hwd / in.)         3.03 x 3.58 x 15.55           Shipping Dimensions (hwd / cm)         7.70 x 9.09 x 39.50           Shipping Weight (lbs.)         1.78           Shipping Weight (kg)         0.81           Unit Dimensions (hwd / cm)         3.18 x 4.12 x 30.48           Unit Weight (lbs.)         1.28           Unit Weight (lbs.)         0.58	Output Receptacles	(4) 5-15R	
Right-Angle Outlets         No           Quitet Spacing         1.77 in.           USER INTERFACE, ALERTS & CONTROLS           Switches         Lighted 2 position switch controls power to all outlets           Locking Switch Cover         Tansparent on/off switch cover prevents accidental turn-off           PHYSICAL           Color         Sliver           Material of Construction         Aluminum           Power Cord Color         Black           Form Factors Supported         Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications           Housing Color         Sliver           Included Mounting Accessories         Includes mounting clips           Mounting Holes or Slots         No           Outlets Measurement (Center to Center)         1.77 in.           Receptacle Color         Black           Shipping Dimensions (hwd / in.)         3.03 x 3.58 x 15.55           Shipping Qimensions (hwd / cm)         7.70 x 9.09 x 39.50           Shipping Weight (bs.)         1.78           Shipping Weight (kg)         0.81           Unit Dimensions (hwd / cm)         3.18 x 4.12 x 30.48           Unit Weight (lbs.)         1.28           Unit Weight (lbs.)         0.58	Circuit Breaker (amps)	15	
Outlet Spacing         1.77 in.           USER INTERFACE, ALERTS & CONTROLS           Switches         Lighted 2 position switch controls power to all outlets           Locking Switch Cover         Transparent on/off switch cover prevents accidental turn-off           PHYSICAL           Color         Silver           Material of Construction         Aluminum           Power Cord Color         Black           Form Factors Supported         Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications           Housing Color         Silver           Included Mounting Accessories         Includes mounting clips           Mounting Holes or Slots         No           Outlets Measurement (Center to center)         1.77 in.           Receptacle Color         Black           Shipping Dimensions (hwd / in.)         3.03 x 3.58 x 15.55           Shipping Weight (lbs.)         1.78           Shipping Weight (lbs.)         1.78           Shipping Weight (kg)         0.81           Unit Dimensions (hwd / cm)         3.18 x 4.12 x 30.48           Unit Weight (lbs.)         1.28           Unit Weight (kg)         0.58	Transformer Accommodation	(2) Yes	
Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off  PHYSICAL  Color Silver Material of Construction Aluminum Power Cord Color Black Form Factors Supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Housing Color Silver Included Mounting Accessories Includes mounting clips Mounting Holes or Slots No Outlets Measurement (Center to Center) 1,77 in.  Receptacle Color Black Shipping Dimensions (hwd / in.) 3.03 x 3.58 x 15.55 Shipping Dimensions (hwd / in.) 7.70 x 9.09 x 39.50 Shipping Weight (lbs.) 1.78 Shipping Weight (kg) 0.81 Unit Dimensions (hwd / orn) 1.250 x 1.620 x 12.000 Unit Weight (kg) 1.28 Unit Weight (kg) 0.58	Right-Angle Outlets	No	
Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off  PHYSICAL  Color Silver  Material of Construction Aluminum  Power Cord Color Black  Form Factors Supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications  Housing Color Silver  Included Mounting Accessories Includes mounting clips  Mounting Holes or Slots No  Outlets Measurement (Center to Center) Black  Shipping Dimensions (hwd / in.) 3.03 x 3.58 x 15.55  Shipping Dimensions (hwd / rm) 7.70 x 9.09 x 39.50  Shipping Weight (lbs.) 1.78  Shipping Weight (kg) 0.81  Unit Dimensions (hwd / rm) 3.18 x 4.12 x 30.48  Unit Weight (kg) 1.28  Unit Weight (kg) 0.58	Outlet Spacing	1.77in.	
Details Switch Cover Transparent on/off switch cover prevents accidental turn-off  PHYSICAL  Color Silver Aluminum  Power Cord Color Black  Form Factors Supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications  Housing Color Silver Included Mounting Accessories Includes mounting clips  Mounting Holes or Slots No  Outlets Measurement (Center to Center) Black  Receptacle Color Black  Shipping Dimensions (hwd / in.) 3.03 x 3.58 x 15.55  Shipping Dimensions (hwd / orm) 7.70 x 9.09 x 39.50  Shipping Weight (lbs.) 1.78  Shipping Weight (kg) 0.81  Unit Dimensions (hwd / in.) 1.250 x 1.620 x 12.000  Unit Weight (kg) 0.58	USER INTERFACE, ALERTS & CONTROLS		
PHYSICAL  Color Silver  Material of Construction Aluminum  Power Cord Color Black  Form Factors Supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications  Housing Color Silver  Included Mounting Accessories Includes mounting clips  Mounting Holes or Slots No  Outlets Measurement (Center to Center to Black  Shipping Dimensions (hwd / in.) 3.03 x 3.58 x 15.55  Shipping Dimensions (hwd / cm) 7.70 x 9.09 x 39.50  Shipping Weight (lbs.) 1.78  Shipping Weight (kg) 0.81  Unit Dimensions (hwd / cm) 3.18 x 4.12 x 30.48  Unit Weight (kg) 0.58	Switches	Lighted 2 position switch controls power to all outlets	
Color Silver  Material of Construction Aluminum  Power Cord Color Black  Form Factors Supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications  Housing Color Silver  Included Mounting Accessories Includes mounting clips  Mounting Holes or Slots No  Outlets Measurement (Center to Center)  Receptacle Color Black  Shipping Dimensions (hwd / in.) 3.03 x 3.58 x 15.55  Shipping Dimensions (hwd / cm) 7.70 x 9.09 x 39.50  Shipping Weight (lbs.) 1.78  Shipping Weight (kg) 0.81  Unit Dimensions (hwd / cm) 3.18 x 4.12 x 30.48  Unit Weight (lbs.) 1.28  Unit Weight (kg) 0.58	Locking Switch Cover	Transparent on/off switch cover prevents accidental turn-off	
Material of Construction  Aluminum  Power Cord Color  Black  Form Factors Supported  Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications  Housing Color  Silver  Included Mounting Accessories  Includes mounting clips  Mounting Holes or Slots  No  Outlets Measurement (Center to Center to Shipping Dimensions (hwd / in.)  Shipping Dimensions (hwd / in.)  Shipping Weight (lbs.)  1.78  Shipping Weight (kg)  0.81  Unit Dimensions (hwd / cm)  3.18 x 4.12 x 30.48  Unit Weight (lks)  1.28  Unit Weight (kg)  0.58			
Power Cord Color  Form Factors Supported  Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications  Housing Color  Included Mounting Accessories  Includes mounting clips  Mounting Holes or Slots  No  Outlets Measurement (Center to Center to Palack  Shipping Dimensions (hwd / in.)  3.03 x 3.58 x 15.55  Shipping Dimensions (hwd / cm)  7.70 x 9.09 x 39.50  Shipping Weight (lbs.)  1.78  Shipping Weight (kg)  0.81  Unit Dimensions (hwd / cm)  3.18 x 4.12 x 30.48  Unit Weight (lbs.)  1.28  Unit Weight (kg)  0.58	Color	Silver	
Form Factors Supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications  Housing Color Silver  Included Mounting Accessories Includes mounting clips  Mounting Holes or Slots No  Outlets Measurement (Center to Center) 1.77 in.  Receptacle Color Black  Shipping Dimensions (hwd / in.) 3.03 x 3.58 x 15.55  Shipping Dimensions (hwd / cm) 7.70 x 9.09 x 39.50  Shipping Weight (lbs.) 1.78  Shipping Weight (kg) 0.81  Unit Dimensions (hwd / cm) 3.18 x 4.12 x 30.48  Unit Weight (lbs.) 1.28  Unit Weight (kg) 0.58	Material of Construction	Aluminum	
Housing Color Included Mounting Accessories Includes mounting clips Mounting Holes or Slots No Outlets Measurement (Center to Center) Exceptacle Color Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / cm) 1.250 x 1.620 x 12.000 Unit Weight (lbs.) 1.28 Unit Weight (kg) 0.58	Power Cord Color	Black	
Included Mounting Accessories  Mounting Holes or Slots  No  Outlets Measurement (Center to Center)  1.77 in.  Receptacle Color  Black  Shipping Dimensions (hwd / in.)  3.03 x 3.58 x 15.55  Shipping Dimensions (hwd / cm)  7.70 x 9.09 x 39.50  Shipping Weight (lbs.)  1.78  Shipping Weight (kg)  0.81  Unit Dimensions (hwd / cm)  3.18 x 4.12 x 30.48  Unit Weight (lbs.)  1.28  Unit Weight (kg)  0.58	Form Factors Supported	Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications	
Mounting Holes or Slots  Outlets Measurement (Center to Center)  1.77 in.  Receptacle Color  Black  Shipping Dimensions (hwd / in.)  3.03 x 3.58 x 15.55  Shipping Dimensions (hwd / cm)  7.70 x 9.09 x 39.50  Shipping Weight (lbs.)  1.78  Shipping Weight (kg)  0.81  Unit Dimensions (hwd / cm)  3.18 x 4.12 x 30.48  Unit Weight (lbs.)  1.28  Unit Weight (kg)  0.58	Housing Color	Silver	
Outlets Measurement (Center to Center)       1.77 in.         Receptacle Color       Black         Shipping Dimensions (hwd / in.)       3.03 x 3.58 x 15.55         Shipping Dimensions (hwd / cm)       7.70 x 9.09 x 39.50         Shipping Weight (lbs.)       1.78         Shipping Weight (kg)       0.81         Unit Dimensions (hwd / in.)       1.250 x 1.620 x 12.000         Unit Dimensions (hwd / cm)       3.18 x 4.12 x 30.48         Unit Weight (lbs.)       1.28         Unit Weight (kg)       0.58	Included Mounting Accessories	Includes mounting clips	
Center)       1.77 III.         Receptacle Color       Black         Shipping Dimensions (hwd / in.)       3.03 x 3.58 x 15.55         Shipping Dimensions (hwd / cm)       7.70 x 9.09 x 39.50         Shipping Weight (lbs.)       1.78         Shipping Weight (kg)       0.81         Unit Dimensions (hwd / in.)       1.250 x 1.620 x 12.000         Unit Dimensions (hwd / cm)       3.18 x 4.12 x 30.48         Unit Weight (lbs.)       1.28         Unit Weight (kg)       0.58	Mounting Holes or Slots	No	
Shipping Dimensions (hwd / in.)       3.03 x 3.58 x 15.55         Shipping Dimensions (hwd / cm)       7.70 x 9.09 x 39.50         Shipping Weight (lbs.)       1.78         Shipping Weight (kg)       0.81         Unit Dimensions (hwd / in.)       1.250 x 1.620 x 12.000         Unit Dimensions (hwd / cm)       3.18 x 4.12 x 30.48         Unit Weight (lbs.)       1.28         Unit Weight (kg)       0.58	Outlets Measurement (Center to Center)	1.77 in.	
Shipping Dimensions (hwd / cm)       7.70 x 9.09 x 39.50         Shipping Weight (lbs.)       1.78         Shipping Weight (kg)       0.81         Unit Dimensions (hwd / in.)       1.250 x 1.620 x 12.000         Unit Dimensions (hwd / cm)       3.18 x 4.12 x 30.48         Unit Weight (lbs.)       1.28         Unit Weight (kg)       0.58	Receptacle Color	Black	
Shipping Weight (lbs.)       1.78         Shipping Weight (kg)       0.81         Unit Dimensions (hwd / in.)       1.250 x 1.620 x 12.000         Unit Dimensions (hwd / cm)       3.18 x 4.12 x 30.48         Unit Weight (lbs.)       1.28         Unit Weight (kg)       0.58	Shipping Dimensions (hwd / in.)	3.03 x 3.58 x 15.55	
Shipping Weight (kg)       0.81         Unit Dimensions (hwd / in.)       1.250 x 1.620 x 12.000         Unit Dimensions (hwd / cm)       3.18 x 4.12 x 30.48         Unit Weight (lbs.)       1.28         Unit Weight (kg)       0.58	Shipping Dimensions (hwd / cm)	7.70 x 9.09 x 39.50	
Unit Dimensions (hwd / in.)       1.250 x 1.620 x 12.000         Unit Dimensions (hwd / cm)       3.18 x 4.12 x 30.48         Unit Weight (lbs.)       1.28         Unit Weight (kg)       0.58	Shipping Weight (lbs.)	1.78	
Unit Dimensions (hwd / cm)       3.18 x 4.12 x 30.48         Unit Weight (lbs.)       1.28         Unit Weight (kg)       0.58	Shipping Weight (kg)	0.81	
Unit Weight (lbs.) 1.28 Unit Weight (kg) 0.58	Unit Dimensions (hwd / in.)	1.250 x 1.620 x 12.000	
Unit Weight (kg) 0.58	Unit Dimensions (hwd / cm)	3.18 x 4.12 x 30.48	
	Unit Weight (lbs.)	1.28	
Outlet Spacing 1.77 in.	Unit Weight (kg)	0.58	
	Outlet Spacing	1.77 in.	



FEATURES & SPECIFICATIONS		
Antimicrobial	No	
Built-In Circuit Breaker	Yes	
STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL 1363; UL Listed	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.