



# Limit switch body, Limit switches XC Standard, 300 VAC, 10 A, XC2J

ZC2JD1H2

V	la	ı	n	

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch body
Device short name	ZC2J
Body type	Plug-in body
Product compatibility	XC2J
Body material	Metal
Number of poles	1
Contacts type and composition	1 C/O
Contact operation	Snap action
Number of steps	1 1 position
Contacts material	Silver plated contacts

### Complementary

· · · · · · · · · · · · · · · · · ·		
Local display	Without	
Electrical connection	Screw-clamp terminals, clamping capacity: 1 x 0.752 x 1.5 mm²	
Positive opening	Without	
Minimum actuation speed	0.01 m/min	
[le] rated operational current	3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A 0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A	
[Ithe] conventional enclosed thermal current	10 A	
[Ui] rated insulation voltage	500 V conforming to IEC 60947-1 for contact block 300 V conforming to CSA C22.2 No 14 for contact block	
Maximum resistance across terminals	0.25 mOhm conforming to IEC 60255-7 category 3	
Short-circuit protection	10 A cartridge fuse, type gG	
Electrical durability	5000000 cycles, DC-13 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C	
Width	42 mm	

Height	81 mm
Depth	41 mm
Net weight	0.38 kg
Terminals description ISO n°1	(11-12)NC (23-24)NO (21-22)NC (13-14)NO

#### **Environment**

IP degree of protection	IP65
IK degree of protection	IK08
Ambient air temperature for operation	-2570 °C for standard environment
Ambient air temperature for storage	-4070 °C
Environmental characteristic	Standard environment

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1

# Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

### Recommended replacement(s)