



Screw Terminal Blocks

500/ 3 35

terminal block, 3 pole, insulating material: PA, cross-section rating: 2.5 mm², pin spacing: 10.00 mm, mounting hole diameter: 3.5 mm, fixing: screw, voltage rating: 450 V, current rating: 24 A



Order Info

reference number (ref.no.)	123203
PU	1,000
EAN	4028012100637

Type

type	terminal block
number of poles	3 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm ²
connection type	screw

Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	6.0 mm ²
flammability rating	V-2
min. ambient temperature	-40 °C
max. ambient temperature operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0-7.5 mm
assembly contact screw	0,8x4,0 / ⚙ 0,5 Nm
mounting hole diameter	3.5 mm
pin spacing	10.00 mm
fixing	screw

Approvals

acc. to EN 60998	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF

Accessories

500 BZ/ 3	191303
500/ 3 ZEL	196003
ABK 405/ 3	193203
ZEL 110	196420