

PART NUMBER	TITLE	CABLE DESCRIPTION	LENGTH 'L'	CABLE COLOR
2174831212	MINIFIT SR. M-S 150MM 10 AWG LEAD BK Au	1X10AWG DISC PVC BK UL 10669	150±5	BLACK
2174831213	MINIFIT SR. M-S 225MM 10 AWG LEAD BK Au	1X10AWG DISC PVC BK UL 10669	225±5	BLACK
2174831214	MINIFIT SR. M-S 300MM 10 AWG LEAD BK Au	1X10AWG DISC PVC BK UL 10669	300±5	BLACK
2174831215	MINIFIT SR. M-S 450MM 10 AWG LEAD BK Au	1X10AWG DISC PVC BK UL 10669	450±5	BLACK
2174832212	MINIFIT SR. M-S 150MM 10 AWG LEAD RD Au	1X10AWG DISC PVC RD UL 10669	150±5	RED
2174832213	MINIFIT SR. M-S 225MM 10 AWG LEAD RD Au	1X10AWG DISC PVC RD UL 10669	225±5	RED
2174832214	MINIFIT SR. M-S 300MM 10 AWG LEAD RD Au	1X10AWG DISC PVC RD UL 10669	300±5	RED
2174832215	MINIFIT SR. M-S 450MM 10 AWG LEAD RD Au	1X10AWG DISC PVC RD UL 10669	450±5	RED



ITEM	PART#	DESCRIPTION	QTY	UOM
A	428170012	MiniFit Sr M Crp Term 10-12 awg SAu	1	PC

- NOTES:**
1. Crimping to be done as per Molex standards.
 2. The product specification relies on the terminals & wire spec.
 3. Free ends must be stripped, twisted & tinned. The length of tinning is 5±1mm. Tinning dia must be 3.8mm Max.

REVISION			
DATE	REV	DESCRIPTION	CHANGER
2021/02/05	A	INITIAL RELEASE	AS20
DOCUMENT STATUS	P1	RELEASE DATE	2021/02/05 14:38:08

FUNCTIONAL SYMBOLS FA = 0 FE = 0 FP = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		molex
	DIMENSION UNITS mm	SCALE NTS	EC NO: 654859 DRWN: AS20 2021/02/05 CHK'D: RDESAI01 2021/02/05 APPR: RDESAI01 2021/02/05		
DIVISIONAL SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		INITIAL REVISION:		DOCUMENT NUMBER 2174831212
	ANGULAR TOL ± °	DRWN: AS20 2021/02/05 APPR: RDESAI01 2021/02/05		DOC TYPE PSD	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING A4-SIZE	SERIES 217483	DOC PART 000
				MATERIAL NUMBER SEE TABLE	CUSTOMER GENERAL MARKET
					REVISION A
					SHEET NUMBER 1 OF 1