

Technical Data Sheet

USB C Hub 4 Port USB 3.1 Gen1 SuperSpeed Type-B Upstream

Model Number: CG-4PU31C1B1







USB C hub provides 4 USB 3.1 Gen1 ports to include 3 USB-A ports and 1 USB C port. An ideal mini hub for super-speed data transfer in industrial environments! The USB C hub is a generation 1 hub of USB 3.1 supporting Super-Speed 5Gbps data transmission speeds and the reversible type-C port. This hub is self powered with a 2-pin terminal block connector to supply power input of +7 $^{\sim}$ 48V DC sold separately.

Features

- Compliant with USB 3.1 Gen1 Specifications
- Rigid and Wall and DIN Rail Mountable Metal Case
- Provides 4 (1 USB-C and 3 USB-A) downstream facing USB 3.1 ports
- Uses included USB 3.1 A to B cable for upstream data
- Support USB Battery Charging: CDP and DCP modes
- Supports 5Gbps (super-speed), 480Mbps (High-Speed),
 12Mbps (Full-Speed), and 1.5Mbps (low-speed) speeds
- Supports 15KV ESD Surge Protection
- Multi Transaction translators (TT) per hub

Product Information

- Model Number: <u>CG-4PU31C1B1</u>
- Packing List:
 - o 4 Port USB 3.1 Hub
 - o DIN Rail Mounting Clips and Screws
 - o 6ft. USB 3.0 A to B Cable
 - o Paper Installation Guide
- Optional Accessories: Power adapter is sold separately.



				ns

Specifications						
OVERVIEW						
Product Type	USB 3.1 Hub (Backward compatible with USB 2.0/1.1					
Electrical Protections	Supports 15KV ESD Surge Protection					
Mountable	Wall and DIN Rail Mounting (DIN Rail Clips Included)					
Construction	Metal					
Applications	Data Centers, Automotive peripheral installation, Machine Equipment, Kiosk, Office, and others					
Certs / Compatibility	RoHS, CE, FCC, WEEE					
CONNECTIONS						
Type-A Downstream Ports	4 (3 USB-A ports and 1 USB-C port)					
Type-B Upstream Ports	1					
7 – 48V Input Power	2-pin terminal block connector					
AVAILABLE POWER MODES						
Mode 1	Bus					
Mode 2	Self power source (+7~48VDC from 2-pin terminal connector)					
ENVIRONMENTAL						
Operating Temperature	0 to 55°C (32 TO 131°F)					
Operating Humidity	5 to 95% RH					
Storage Temperature	-20°C to 85°C (-4 to 185° F)					
DIMENSIONS						
Length	4.50" (11.45 cm)					
Width	2.26" (5.73 cm)					
Height	1.03" (2.63 cm)					
OS SUPPORT						
Windows	Windows 7, Windows 8, Windows 10					
Other	Linux and Mac OS 10.X					
LED						
Power	1(green)					
Downstream Ports	N/A					
WARRANTY						
Warranty Period	1 year from date of purchase					
PRODUCT URL						
CG-4PU31C1B1 Product Page	https://www.coolgear.com/product/usb-c-hub-4-port-usb-3-1-gen1-superspeed-type-b-upstream					



© 2017 Coolgear, Inc. All Rights Reserved. All products and accompanying digital documentation including images are the property and / or trademarks of Coolgear Inc. Coolgear Inc. are continuously improving upon its products. Product specifications are subject to change without notice.