



DIMENSION

L	Nx7.5
P	(N-1)x7.5

N=Number of poles

Poles	Tolerance	
	DIM L	DIM P
2p-6p	±0.20	±0.15
7p-12p	±0.25	±0.20
13p-18p	±0.30	±0.25
19p-24p	±0.40	±0.30

Material
Terminal body(metal housing): steel stamped
Terminal screw: Steel Zinc plating " " slot type
Contacts: Brass
Surface of solder tail:Tin plated
Insulator(housing): Thermoplastic (UL94V-0) , GREEN

Electrical cULus
Voltage rating: 300VAC
Current rating: 20A
Wire range:
Solid wire(AWG): 12-22
Stranded wire(AWG): 12-22
Torque(Lb-In): 2.4
Screw: M2.5
Wire strip length: 10-11mm
Withstanding Voltage: 1.6KV
Operating temperature: -40°C to +115°C
Soldering temperature: 250°C±10°C/5 Sec
Safety Approval: us

RECOMMENDER PCB LAYOUT

RoHS compliant



File No.: E349947

Scale	1:1
TOLERANCE	
X.	±0.50
X.X	±0.30
X.XX	±0.10
DIM	TOL
X.°	±1°
Angle	TOL
Id.	
Modification	
Date	Name
19.04.2016	Winnie
19.04.2010	Alex

ASSMANN
WSW/ components

Customer-No.
ASSMANN WSW-No.
A-TB750-TRxxV
Drawing-No.
ASS 4099 CO
Replace

rev01
Sheet

1	2	3	4	5	6	7
H	G	F	E	D	C	B