

## External 240V Tower Battery Pack for select Tripp Lite UPS Systems (BP240V557C-1PH)

MODEL NUMBER: **BP240V557C-1PH**



### Highlights

- Extends runtime of compatible Tripp Lite UPS Systems using 240VDC configuration
- Includes built in 7A charger
- Includes UPS connection cabling
- 10 year design life
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Description

Tripp Lite's BP240V557C-1PH External Battery Pack with built-in 7A charger offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Includes heavy gauge cabling to connect to host UPS. Multiple BP240V557C-1PH batteries can be daisy-chained for longer runtime configurations with appropriate contractor-supplied battery pack interconnection cabling (see manual). Internal battery charger is powered via hardwire connection to 120V 30A electrical service.  
**COMPATIBLE UPS SYSTEMS:** SU6000RT3U, SU6000RT3UHV, SU8000RT3U, SU8000RT3U1TF, SU10KRT3U, SU10KRT3UHV, SU10000RT3U, SU10000RT3U2TF and other Tripp Lite UPS systems specifying the use of this battery pack

### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- 10 year design life
- Multiple battery packs can be daisy-chained through each other to the UPS for even longer extended run operation
- Cabling to connect one BP240V557C-1PH is included - cabling for additional battery packs is contractor supplied
- Includes built-in 7A charger powered via hardwire 120VAC 30A input connection

## Specifications

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332146786 |
| BATTERY  |              |

|                                     |  |
|-------------------------------------|--|
| Expandable Runtime                  | Yes  |
| Expandable Runtime Description      | Multiple battery packs can be daisy-chained to the UPS for extended runtime. Configuration specific cabling for multi-battery pack configurations is contractor provided.              |
| DC System Voltage (VDC)             | 240  |
| UPS Connection                      | Included cabling enables connection between unique UPS connector and hardwire DC terminals in battery pack. Cabling to connect multiple external battery packs is contractor provided. |
| <b>PHYSICAL</b>                     |  |
| Material of Construction            | Steel  |
| External Battery Pack Form Factor   | Tower  |
| Shipping Dimensions (hwd / in.)     | 60.00 x 30.50 x 34.00  |
| Shipping Dimensions (hwd / cm)      | 152.40 x 77.47 x 86.36   |
| Shipping Weight (lbs.)              | 1200.00  |
| Shipping Weight (kg)                | 544.31   |
| Unit Dimensions (hwd / in.)         | 60.000 x 30.000 x 32.000   |
| Unit Dimensions (hwd / cm)          | 152.4 x 82.3 x 73.2  |
| Unit Weight (lbs.)                  | 1250   |
| Unit Weight (kg)                    | 566.99   |
| <b>WARRANTY &amp; SUPPORT</b>       |  |
| Product Warranty Period (Worldwide) | 1-year limited warranty  |