

Product data sheet

Specifications



Insulating mounting plate for enclosure H800xW600mm made of polyester

NSYMPP86

Main

Range	Spacial
Accessory / separate part category	Mounting accessory
Product or component type	Mounting plate
Device application	Multi-purpose
Enclosure nominal dimensions	-
Mounting location	Step slide Direct fixing on backstuds
Mounting plate description	Plain
Range compatibility	Spacial (Spacial S3D) Spacial (Spacial CRN) Spacial (Spacial S3X) Thalassa (Thalassa PLM)
Quantity per set	Set of 1
Material	Fibreglass reinforced polyester
Colour	Grey (RAL 7035)

Complementary

Fixing mode	Screwed on backstuds - screw type M8 By fixing element
Permanent permissible load	63.1 kg S3D, CRN, S3X enclosures 63.1 kg PLM enclosure
Maximum load	150 kg PLM enclosure 150 kg S3D, CRN, S3X enclosures
Height	765 mm nominal: 800 mm enclosure nominal dimension:
Width	550 mm nominal: 600 mm enclosure nominal dimension:
Surface and useful surface	42.1 dm ²
Thickness	5 mm
Net weight	3.8 kg
Variant particularity	With enclosures H800 x W1200

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Height	0.5 cm
Package 1 Width	55.0 cm
Package 1 Length	76.5 cm
Package 1 Weight	3.787 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)