SIEMENS

Data sheet

US2:HF362RCR



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. 60A 3P 600V 3W FUSED HD T3R W/CLSR

mechanical service life (switching cycles) typical	10000
fastening method	SURFACE
number of poles	3
suitability for operation	DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS
Electricity	
ampacity	60 A
supply voltage frequency rated value 50/60 Hz	Yes
Environmental conditions	
ambient temperature during operation maximum	85 °C
ambient temperature during operation minimum	-29 °C
Model	
product brand name	SIEMENS
product sub brand name	VBII
product sub brand name product type designation	VBII HEAVY DUTY SWITCH
product type designation	HEAVY DUTY SWITCH
product type designation special product feature	HEAVY DUTY SWITCH FACTORY INSTALLED R FUSE CLIPS
product type designation special product feature type of electrical connection	HEAVY DUTY SWITCH FACTORY INSTALLED R FUSE CLIPS
product type designation special product feature type of electrical connection Mechanical Design	HEAVY DUTY SWITCH FACTORY INSTALLED R FUSE CLIPS MECHANICAL LUGS
product type designation special product feature type of electrical connection Mechanical Design design of the housing	HEAVY DUTY SWITCH FACTORY INSTALLED R FUSE CLIPS MECHANICAL LUGS TYPE 3R
product type designation special product feature type of electrical connection Mechanical Design design of the housing design of the actuating element	HEAVY DUTY SWITCH FACTORY INSTALLED R FUSE CLIPS MECHANICAL LUGS TYPE 3R SINGLE THROW
product type designation special product feature type of electrical connection Mechanical Design design of the housing design of the actuating element material	HEAVY DUTY SWITCH FACTORY INSTALLED R FUSE CLIPS MECHANICAL LUGS TYPE 3R SINGLE THROW

last modified:

9/15/2021 🖸