

# Han-Yellock M-c 1.5mm<sup>2</sup> (Ag)



Part number	11 05 000 6105
Specification	Han-Yellock M-c 1.5mm² (Ag)
HARTING eCatalogue	https://b2b.harting.com/11050006105

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Contacts
Series	Han-Yellock <sup>®</sup>
Type of contact	Crimp contact

#### Version

Manufacturing process Turned contacts	Gender	Male
	Manufacturing process	Turned contacts

#### Technical characteristics

Conductor cross-section	1.5 mm <sup>2</sup>
Conductor cross-section	AWG 16
Operating current	≤20 A
Contact resistance	≤2 mΩ
Stripping length	6.5 mm

## Material properties

• •	
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained

Page 1 / 2 | Creation date 2023-02-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



# Material properties

REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

Specifications	IEC 60664-1
Specifications	IEC 61984

### Commercial data

Packaging size	100
Net weight	0.696 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140109360
eCl@ss	27440204 Contact for industrial connectors