

Magnetic interference detection.

Anti tamper switch. Can be made to grade 2 with bypass jumper.

Interchangeable resistors for most popular panels.

Spacer and mounting screws supplied.

Supervised EOL.

Can be fitted in shared zone.

Features Include		Specifications	
Resistors to suit most panels		 BE EN50131-2-8 Approved. 	
 Magnetically shielded. Grade 3 or 2 if required Can be paired in a zone. 		• Grade 3.	
Did you know we also sell?		 Monitoring loop. 	
	🕒 🐲 🐄 🗳	 Selectable resistor jumpe 	ers.
Float Switches Pressure Switch	Reed Solid Sta ches Magnets Proximity Switches Switches Reed Relays Relays		k operating gap.
Rev. No.	Revision Note	Date	Signature
1	Datasheet	23-09-15	ML
	As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.		
OULUTY MINAGEMINT 003	Phone : +44 (0)1255 862236	www.comus-intl.com	Fax: +44 (0)1255 862014
D 9001:2008 rtificate No. FM21080	©2015 Copyright Comus Europe Ltd, Unit 7, Rice Bridge Industrial Estate, Thorpe - Le - Soken, Essex, CO16 0HL, ENGLAND.		

5 Copyright Comus Europe Ltd, Unit 7, Rice Bridge Industrial Estate, Thorpe - Le - Soken, Essex, CO16 0HL, ENG USA: Comus International:+1 973 777 6900, Belgium: Comus Belgium BVBA: +32 (0)12 390400