

Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 10.1 mm, Rated cross-section: 4 mm², Colour: Black

RAL: 9005

Business data

| Article number | <u>3720.4</u> | |
|--|---------------------------|--|
| Article name | ZQI 4/2 BK | |
| GTIN (EAN) | 4044211111403 | |
| Packaging unit | 50 | |
| Quantity unit | PC | |
| Weight per piece (not including packaging) | 1.32 g | |
| Weight per piece (including packaging) | 1.34 g | |
| Unit of weight | G | |
| Customs number | 85389099 | |
| Country of origin | CZ | |
| Prio-Article | 3720.8 | |
| Product description | Insulated cross-connector | |
| | | |

Data sheet 3720.4 ZQI 4/2 BK



Technical data

| Dimensions | |
|----------------------------------|-------------------|
| Length | 4.5 mm |
| Width | 10.1 mm |
| Pitch size | 6 mm |
| Ratings | |
| Voltage with partition, max. | 800 V |
| Voltage without partition, max. | 800 V |
| Rated current | 32 A |
| Rated cross-section | 4 mm ² |
| Contamination degree | 3 |
| Connection data | |
| No. of poles | 2 |
| Materials | |
| Material | Copper alloy |
| Surface | Tin-plated |
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-2 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 105 °C |
| Further technical data | |
| Mounting type | Plug in |
| Insulation available | \checkmark |
| Touch protection is available | \checkmark |
| Number of bridged terminals | 2 |
| Environmental Product Compliance | |
| REACH Conform | yes |
| REACH Reference date | 2022-06-10 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

Data sheet 3720.4 ZQI 4/2 BK

CONTACLIP

Media

Data sheet 3720.4 ZQI 4/2 BK



Accessories

##INVERSE##CONTA-CONNECT

| | Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige | | | | |
|--|--|----------------|---------------|-------------------|--|
| | Article number | Article name | GTIN (EAN) | Packaging unit | |
| | 3515.2 | ZRK 4/2A BG | 4044211151751 | 100 | |
| | Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige | | | | |
| | Article number | Article name | GTIN (EAN) | Packaging unit | |
| | 1716.2 | ZRK 4/2A Ex BG | 4044211058579 | 100 | |
| | Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige | | | | |
| | Article number | Article name | GTIN (EAN) | Packaging unit | |
| | <u>1717.2</u> | ZRK 4/3A Ex BG | 4044211058609 | 100 | |
| | Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige | | | | |
| | Article number | Article name | GTIN (EAN) | Packaging unit | |
| | 3516.2 | ZRK 4/3A BG | 4044211151775 | 100 | |
| | Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige | | | | |
| | Article number | Article name | GTIN (EAN) | Packaging unit | |
| | 1718.2 | ZRK 4/4A Ex BG | 4044211058630 | 100 | |
| | Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige | | | | |
| | Article number | Article name | GTIN (EAN) | Packaging unit | |

3517.2

ZRK 4/4A BG

4044211151782

100