

## External 192V Battery Pack For SU5000RT4U, SU6000RT4U & SU8000RT4U - Tower, TAA

MODEL NUMBER: **BP192V787C-1PH**



TAA-compliant external 192V battery pack provides extended runtime for compatible Tripp Lite UPS systems.

### Features

**192V Battery Pack Gives Your Compatible Tripp Lite UPS System Extended Runtime**The BP192V787C-1PH is compatible with Tripp Lite's SU5000RT4U, SU6000RT4U, SU8000RT4U and other UPS systems that specify the use of this 192-volt battery pack. Not only does it provide extended runtime, but it can also be daisy-chained with user-supplied cabling to additional external battery packs for even longer extended-run operation. Heavy-gauge cabling is included for simple connecting to the host UPS system.

**Designed and Constructed to Ensure Consistent Power for a Long Time**This 192V battery pack is made from heavy-gauge welded steel with a baked powder-coated finish that protects the cabinet from chipping and corrosion. The hinged cabinet door locks to prevent tampering and to facilitate easy access to the internal batteries. A built-in 7A charger is powered via hardwire connection to 120V 30A or 208/240V 20A electrical service at 60 Hz. User-supplied power output cables feed into the cabinet through conduit knockouts built into the cabinet's exterior.

**TAA-Compliant for GSA Schedule Purchases**The BP192V787C-1PH is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

**One-Year Warranty**The BP192V787C-1PH is backed by a one-year warranty, ensuring reliability and performance.

## Specifications

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332203601 |
| INPUT    |              |

### Highlights

- Connects to expandable 192V DC Tripp Lite UPS systems for extended runtime
- Daisy-chain connector supports additional battery packs for even longer runtime
- Built-in 7A charger is powered via hardwire connection to electrical service at 60 Hz
- Designed with heavy-gauge steel to provide consistent power for a long time
- Complies with Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Applications

- Extend the runtime of your compatible Tripp Lite UPS system in a data center or telecom network
- Daisy-chain to additional battery packs to provide even longer extended-run operation in mission-critical environments, such as emergency or security systems

### System Requirements

- SU5000RT4U, SU6000RT4U or SU8000RT4U UPS system

### Package Includes

- BP192V787C-1PH External 192V Battery Pack For SU5000RT4U, SU6000RT4U & SU8000RT4U
- Heavy-gauge UPS connection cable
- Owner's manual

|   |  |
|---|--|
| Input Phase   | Single-Phase   |
| Maximum Input Amps Details                                    | Built-in 7A battery charger requires 60Hz 120V (26A max) or 208/240V (16A max) input   |
| Input Connection Type   | Hardwire AC input (input cabling is contractor supplied)   |
| Voltage Compatibility (VAC)                                   | 120; 208/240   |
| Input Frequency   | 60Hz   |
| <b>BATTERY</b>  |  |
| Expandable Runtime  | Yes  |
| Expandable Runtime Description                                | Multiple battery packs can be daisy-chained to the UPS for extended runtime. Configuration specific cabling for multi-battery pack configurations is contractor provided.              |
| DC System Voltage (VDC)                                       | 192  |
| UPS Connection  | Included cabling enables connection between unique UPS connector and hardwire DC terminals in battery pack. Cabling to connect multiple external battery packs is contractor provided. |
| <b>PHYSICAL</b>   |  |
| Material of Construction                                      | Metal  |
| External Battery Pack Form Factor                             | Tower  |
| Installation Form Factors Supported with Included Accessories | Tower  |
| Shipping Dimensions (hwd / in.)                               | 66.00 x 46.00 x 48.00  |
| Shipping Dimensions (hwd / cm)                                | 167.64 x 116.84 x 121.92   |
| Shipping Weight (lbs.)  | 1656.00  |
| Shipping Weight (kg)  | 751.15   |
| Unit Dimensions (hwd / in.)                                   | 59.000 x 29.000 x 31.500   |
| Unit Dimensions (hwd / cm)                                    | 149.9 x 73.7 x 80  |
| Unit Weight (lbs.)  | 1546   |
| Unit Weight (kg)  | 701.25   |
| <b>STANDARDS &amp; COMPLIANCE</b>                             |  |
| Product Compliance  | RoHS; CE (Europe); Trade Agreements Act (TAA)  |
| <b>WARRANTY &amp; SUPPORT</b>                                 |  |
| Product Warranty Period (Worldwide)                           | 1-year limited warranty  |



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States



© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.